

XA-series, air driven hydraulic pumps



- Ergonomic design for less operator fatigue
- Variable oil flow & fine metering for precise control
- Higher oil flow for increased productivity
- Closed hydraulic system prevents contamination and allows pump usage in any position
- Pedal lock function for retract position
- Ground screw for improved ATEX explosion safety
- External adjustable pressure setting valve
- Two speed pump

For use with cylinder		Usable Oil Capacity	Model Number*	Output Flow Rate		Pressure Gauge	3/3 control valve	4/3 control valve	Dynamic Air Pressure	Weight
S/A	D/A			l/min						
		litres		No Load	Load				bar	kg
•	-	1,0	XA11	2,0	0,25	-	•	-	2,1 - 8,6	8,6
•	-	2,0	XA12	2,0	0,25	-	•	-	2,1 - 8,6	10,2
•	-	1,0	XA11G	2,0	0,25	•	•	-	2,1 - 8,6	8,8
•	-	2,0	XA12G	2,0	0,25	•	•	-	2,1 - 8,6	10,4
-	•	1,0	XA11V	2,0	0,25	-	-	•	2,1 - 8,6	10,1
-	•	2,0	XA12V	2,0	0,25	-	-	•	2,1 - 8,6	11,7
-	•	1,0	XA11VG	2,0	0,25	•	-	•	2,1 - 8,6	10,3
-	•	2,0	XA12VG	2,0	0,25	•	-	•	2,1 - 8,6	11,9

* High-Flow coupler CR400 and accessories must be ordered separately

see xvari.com for more information on this pump