

PME, PMU-series, portable electric torque wrench pumps



Powerful two-speed pump, lightweight, easy to carry
 Standard heat exchanger package on PMU-models keeps the oil cool under extreme use
 Glycerine filled gauge with scales reading in bar and psi
 Transparent overlays in Nm and Ft.Ibs for all Enerpac torque wrenches provide a quick torque reference
 Adjustable pressure relief valve for accurate torque adjustments and precise repeatability
 700 bar pumps: for use with Enerpac S and W-series or other wrenches
 800 bar pumps: for use with Enerpac SQD and HXD-series or other wrenches

Oil Flow Rate	Maximum Operating Pressure	Model Number	Model Number with Heat Exchanger *	Usable Oil Capacity	Motor Voltage	Weight*
				litres		
l/min	bar				(A-V-Ph-Hz)	kg
1st / 2nd stage	1st / 2nd stage					
3,3 / 0,34	50 / 700	PME-10422-Q	PMU-10422-Q	2,8	9-230-1-50/60	17
3,3 / 0,34	50 / 700	PME-10427-Q	PMU-10427-Q	2,8	9-115-1-50/60	17
3,3 / 0,34	50 / 800	PME-10422	PMU-10422	2,8	9-230-1-50/60	17
3,3 / 0,34	50 / 800	PME-10427	PMU-10427	2,8	9-115-1-50/60	17

* PMU pump with heat exchanger weights 24 kg.