

ZA4T-series, air hydraulic torque wrench pumps



- ATEX 95 certified for use in potentially explosive atmospheres
- For use with any brand of 700 or 800 bar hydraulic torque wrenches
- Standard heat exchanger warms exhaust air to prevent freezing and cools the hydraulic oil
- Standard Air Regulator-Filter-Lubricator
- Gauge with transparent overlays for Enerpac torque wrenches provide a quick torque reference
- User adjustable pressure relief valve
- Z-class high efficiency pump: two speed, high by-pass pressure reduces torque cycles for improved productivity
- Options: skidbar, roll bar, 4-wrench manifold for simultaneous operation of multiple wrenches

[view Z-Class video \(or click here to download\)](#)

Output Flow Rate					Model Number	Useable Oil Capacity	Dynamic Air Pressure	Weight
l/min								
at	at	at	at	at				
7 bar	50 bar	350 bar	700 bar	800 bar		litres	bar	kg
9,8	8,2	1,3	1,0	-	ZA4204TX-Q	4,0	4,1 - 6,9	42
9,8	8,2	1,3	1,0	-	ZA4208TX-Q	8,0	4,1 - 6,9	47
9,8	8,2	1,3	1,0	-	ZA4204TX-QR	4,0	4,1 - 6,9	45
9,8	8,2	1,3	1,0	-	ZA4208TX-QR	8,0	4,1 - 6,9	50
9,8	8,2	1,3	1,0	0,9	ZA4204TX-E	4,0	4,1 - 6,9	42
9,8	8,2	1,3	1,0	0,9	ZA4208TX-E	8,0	4,1 - 6,9	47
9,8	8,2	1,3	1,0	0,9	ZA4204TX-ER	4,0	4,1 - 6,9	45
9,8	8,2	1,3	1,0	0,9	ZA4208TX-ER	8,0	4,1 - 6,9	50