

ZU4T-series classic torque wrench pump



- ZU4T-Classic torque wrench pumps has traditional electro-mechanical components (transformers, relays and switches) in place of LCD with solid-state electronics on the ZU4T premium wrench pumps
- Shut-off timer, turns pump off after 20 seconds, to conserve power and reduce heat
- For use with S and W-series Enerpac torque wrenches and other major brands 700 bar wrenches
- Pump options: heat exchanger, skid bar, roll cage and 4-wrench manifold

[view Z-Class video \(or click here to download\)](#)

Oil Flow				Model Number	Model Number with Heat Exchanger	Usable Oil Capacity	Motor	Weight
l/min								
at								
7 bar	50 bar	350 bar	700 bar			litres	Volt - phase	kg
11,5	8,8	1,2	1,0	ZU4204BB-Q	-	4,0	115 - 1	32
11,5	8,8	1,2	1,0	-	ZU4204BB-QH	4,0	115 - 1	37
11,5	8,8	1,2	1,0	ZU4208BB-Q	-	8,0	115 - 1	36
11,5	8,8	1,2	1,0	-	ZU4208BB-QH	8,0	115 - 1	40
11,5	8,8	1,2	1,0	ZU4204BE-Q	-	4,0	230 - 1	32
11,5	8,8	1,2	1,0	-	ZU4204BE-QH	4,0	230 - 1	37
11,5	8,8	1,2	1,0	ZU4208BE-Q	-	8,0	230 - 1	36
11,5	8,8	1,2	1,0	-	ZU4208BE-QH	8,0	230 - 1	40