

## ZU4T-series, Z-class, electric torque wrench pumps



- For all major brands of 700 and 800 bar single- or double-acting torque wrenches
- Z-Class high-efficiency pump design; higher oil flow and bypass pressure, cooler running and requires 18% less current draw than comparable pumps
- Powerful 1,25 kW universal motor, high power-to-weight ratio, excellent low-voltage operating characteristics
- Low-voltage pendant provides additional safety for the operator (remote control units)
- LCD readout provides pressure display and a number of diagnostic and readout capabilities never before offered on a portable electric pump
- Auto cycle feature provides continuous wrench cycle operation
- Options: skidbar, heat exchanger and 4-wrench manifold for simultaneous multi-wrench operation

[view Z-Class video \(or click here to download\)](#)

Oil Flow l/min				Model Number	Useable Oil Capacity	Motor Voltage at 50 or 60 Hz	Weight
7	50	700	800				
bar	bar	bar	bar		litres	Volt-phase	kg
11,5	8,8	1,0	-	ZU4204TB-E	4,0	115 - 1	32
11,5	8,8	1,0	-	ZU4208TB-E	8,0	115 - 1	36
11,5	8,8	1,0	-	ZU4204TE-E	4,0	230 - 1	32
11,5	8,8	1,0	-	ZU4208TE-E	8,0	230 - 1	36
11,5	8,8	1,0	0,9	ZU4204TB-Q	4,0	115 - 1	32
11,5	8,8	1,0	0,9	ZU4208TB-Q	8,0	115 - 1	36
11,5	8,8	1,0	0,9	ZU4204TE-Q	4,0	230 - 1	32
11,5	8,8	1,0	0,9	ZU4208TE-Q	8,0	230 - 1	36