

SQD-series, square drive aluminum wrenches



- Very high torque-to-weight ratio
- High speed, double-acting operation
- High degree of rotation angle
- Never-jam mechanism
- High repeatability, with accuracy $\pm 3\%$
- Slim nose radius and 360° swivel hose connection allow easier positioning in confined areas
- Few moving parts means durability and low maintenance
- Push-button drive release; no tools needed to reverse square or Allen-key drives for tightening or loosening
- Optional Allen-Key drives 14 - 70 mm, 1/2 - 2 1/4 inch

Typical Socket Size Range		Square Drive	Maximum Torque * at 800 bar		Model Number	Weight **	Optional Allen-Key Drive Range	
mm	inch		Nm	Ft.lbs			kg	mm
15 - 50	11/16 - 1 7/8	3/4	2350	1735	SQD-25-I	2,5	14 - 24	1/2 - 1
20 - 100	7/8 - 3 7/8	1	4800	3550	SQD-50-I	4,3	17 - 32	5/8 - 1 1/4
30 - 110	1 1/8 - 4 3/8	1 1/2	7560	5570	SQD-75-I	6,7	17 - 32	5/8 - 1 1/4
40 - 120	1 5/8 - 4 3/4	1 1/2	10000	7360	SQD-100-I	8,0	22 - 36	7/8 - 1 1/2
60 - 155	2 3/8 - 6 1/8	1 1/2	16000	11835	SQD-160-I	12,0	30 - 46	1 1/4 - 1 3/4
80 - 255	3 1/8 - 10	2 1/2	27000	19875	SQD-270-I	24,5	36 - 70	1 1/2 - 2 1/4

* Determine maximum torque according to the bolt (nut) size and grade.

** Weight including reaction arm and square drive.