

Cordless combi

GSB 14.4 VE-2 Professional

Fast and robust. For medium to large screw and drilling diameters

- Specially balanced gear ratio for fast work progress when drilling and impact drilling
- Extremely robust: fully functional, even after falling from a height of 2 m onto concrete, thanks to the "Dura Shield" housing
- Long lifetime due to the new, unique Bosch high-performance motor

- Progressively increasing torque enables fine adjustment to any size of screw
- Newly developed Auto-Lock drill chuck with high clamping force for screwdriver bits and drill bits
- Ergonomically shaped handle with comfort zone in the soft grip area for a secure hold and low-fatigue working
- Changeable carbon brushes
- 25 torque settings + drill setting

Scope of delivery

Part no. 0 601 994 H00

- Quick Charger AL 1450 DV (2 607 224 702)
- 2 x 2.6 Ah NiMH batteries (2 607 335 686)
- Carrying case (2 605 438 596)
- Keyless chuck 13 mm (2 608 572 247)

Drill chuck, version Keyless chuck

Technical data

Torque, max. (hard screw driving applications) 65 Nm

Torque, max. (soft screw driving applications) 28 Nm

No-load speed (1st gear/2nd gear) 0 – 470 / 1.950 rpm

Max. impact rate 29.000 bpm

Chuck jaw width, min. /max. 1,5 / 13 mm

Drill spindle thread 1/2"

Battery voltage 14,4 V

Weight incl. battery 2,8 kg

Keyless chuck 13 mm

Charging time, approx. 30 min

Torque settings 25+1

Length 272,0 mm

Height 266,0 mm

Drilling diameter

Max. drilling diameter in wood 40 mm

Max. drilling diameter in steel 13 mm

Max. drilling diameter in masonry 14 mm

Screw diameter

Max. screw diameter 10 mm

Functions

- Multiple gears
- Impact drilling
- Forward/reverse operation
- Auto-Lock
- Soft grip