

Cordless combi

GSB 18 VE-2 Professional

Fast and robust. For medium to large screw and drilling diameters

- Specially balanced gear ratio for fast work progress when drilling and impact drilling
- Extremely robust: fully functional, even after falling from a height of 2 m onto concrete, thanks to the "Dura Shield" housing
- Long lifetime due to the new, unique Bosch high-performance motor

- Progressively increasing torque enables fine adjustment to any size of screw
- Newly developed Auto-Lock drill chuck with high clamping force for screwdriver bits and drill bits
- Ergonomically shaped handle with comfort zone in the soft grip area for a secure hold and low-fatigue working
- Changeable carbon brushes
- 25 torque settings + drill setting

Scope of delivery

Part no. 0 601 994 F00

- Quick Charger AL 2450 DV (2 607 225 028)
- 2 x 2.6 Ah NiMH batteries (2 607 335 688)
- Carrying case (2 605 438 617)
- Keyless chuck 13 mm (2 608 572 247)
- Auxiliary handle (2 602 025 169)

Drill chuck, version Keyless chuck

Technical data

Torque, max. (hard screw driving applications) 75 Nm

Torque, max. (soft screw driving applications) 36 Nm

No-load speed (1st gear/2nd gear) 0 – 500 / 2.050 rpm

Max. impact rate 31.000 bpm

Chuck jaw width, min. /max. 1,5 / 13 mm

Drill spindle thread 1/2"

Battery voltage 18 V

Weight incl. battery 3 kg

Keyless chuck 13 mm

Charging time, approx. 30 min

Torque settings	25+1
Length	272,0 mm
Height	266,0 mm

Drilling diameter

Max. drilling diameter in wood	45 mm
Max. drilling diameter in steel	13 mm
Max. drilling diameter in masonry	16 mm

Screw diameter

Max. screw diameter	10 mm
---------------------	-------

Functions

- Multiple gears
- Impact drilling
- Forward/reverse operation
- Auto-Lock
- Soft grip