



## Crimped Wire Wheel Brushes - Narrow Face - 3-5" Diameter - Stainless Steel

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

Advance manufactures a complete range of individual filament, crimped wire wheels for individual or gang-mounted use. Features include heavy fill density for more wire points, which means more brushing action and longer life; oil tempered, industrial quality wire, and uniform wire disbursement for optimal balance and finish. Choose from Narrow, Medium and Wide Face models, with an additional selection of wheels manufactured exclusively for bench and pedestal grinders.

Narrow Face Advance crimped wire wheels are used for light to medium duty brushing action. Designed for individual use in confined areas, or in assemblies mounted on a shaft. They are best suited for brushing uneven surfaces and areas inaccessible to wider brushes. Ideal for removal of light scale, dirt, rust, corrosion and light burs on non-ductile materials

3", 4" and 5" diameter single-section Advance narrow face crimped wire wheels are available in a variety of wire sizes from .006 to .020 for applications requiring various degrees of removal rates and surface finishing demands.



EDP	Brush Diameter	Arbor Hole	Wire Size	Trim Length	Face Width	Max. RPM	Compatible Adapter Style	
80330	3	1/2-3/8	.006	3/4	9/16	10,000	Plain Round	<a href="#">Request Info</a>
80331	3	1/2-3/8	.008	3/4	9/16	10,000	Plain Round	<a href="#">Request Info</a>
80332	3	1/2-3/8	.010	3/4	9/16	10,000	Plain Round	<a href="#">Request Info</a>
80333	3	1/2-3/8	.014	3/4	9/16	10,000	Plain Round	<a href="#">Request Info</a>
80338	4	1/2-3/8	.006	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80339	4	1/2-3/8	.008	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80340	4	1/2-3/8	.010	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80341	4	1/2-3/8	.012	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80342	4	1/2-3/8	.014	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80343	4	1/2-3/8	.020	3/4	9/16	12,500	Plain Round	<a href="#">Request Info</a>
80344	4	5/8-1/2	.006	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>
80345	4	5/8-1/2	.008	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>
80346	4	5/8-1/2	.010	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>
80347	4	5/8-1/2	.012	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>
80348	4	5/8-1/2	.014	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>

80349 4	5/8-1/2	.020	3/4	1/2	12,500	Plain Round	<a href="#">Request Info</a>
80356 5	5/8-1/2	.006	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>
80357 5	5/8-1/2	.008	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>
80358 5	5/8-1/2	.010	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>
80359 5	5/8-1/2	.012	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>
80360 5	5/8-1/2	.014	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>
80361 5	5/8-1/2	.020	1-1/4	7/8	10,000	Plain Round	<a href="#">Request Info</a>