



Crimped Wire Wheel Brushes - Wide Face - 4-1/4" to 8" Diameter - Stainless Steel

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

Advance manufactures a complete range of individual filament, crimped wire wheels for individual or gang-mounted use. Features include heavy fill density for more wire points, which means more brushing action and longer life; oil tempered, industrial quality wire, and uniform wire disbursement for optimal balance and finish. Choose from Narrow, Medium and Wide Face models, with an additional selection of wheels manufactured exclusively for bench and pedestal grinders.

Advance wide face, multiple section brushes are for all-purpose portable or stationary brushing, and designed for maximum productivity. Engineered for professional use, the wide face brushes feature precision balance, high quality tempered wire, and dense wire fill for fast brushing action, superior surface finish and long service life. Available in a wide product range to fit every application, including: refining metal surfaces, preparing rubber in vulcanizing, blending surfaces, and removing light burrs, paint and corrosion

Advance selection range of 4-1/4" through 8" diameter wide face crimped wire wheels manufactured with Stainless Steel wire.



EDP	Brush Diameter	Arbor Hole	Wire Size	Trim Length	Face Width	Max. RPM	Compatible Adapter Style	
81264	4-1/4	2	.006	7/8	1-1/8	8,000	Style C	Request Info
81266	4-1/4	2	.010	7/8	1-1/8	8,000	Style C	Request Info
81267	4-1/4	2	.012	7/8	1-1/8	8,000	Style C	Request Info
81268	4-1/4	2	.014	7/8	1-1/8	8,000	Style C	Request Info
81276	6	2	.006	1-1/8	1-1/8	6,000	Style C	Request Info
81277	6	2	.008	1-1/8	1-1/8	6,000	Style C	Request Info
81278	6	2	.010	1-1/8	1-1/8	6,000	Style C	Request Info
81279	6	2	.012	1-1/8	1-1/8	6,000	Style C	Request Info
81280	6	2	.014	1-1/8	1-1/8	6,000	Style C	Request Info
81283	7	2	.008	1-5/16	1-7/16	6,000	Style C	Request Info
81285	7	2	.012	1-5/16	1-7/16	6,000	Style C	Request Info
81286	7	2	.014	1-5/16	1-7/16	6,000	Style C	Request Info
81288	8	2	.006	1-1/2	1-5/8	4,500	Style B	Request Info
81289	8	2	.008	1-1/2	1-5/8	4,500	Style B	Request Info
81290	8	2	.010	1-1/2	1-5/8	4,500	Style B	Request Info
81291	8	2	.012	1-1/2	1-5/8	4,500	Style B	Request Info
81292	8	2	.014	1-1/2	1-5/8	4,500	Style B	Request Info
81293	8	2	.020	1-1/2	1-5/8	4,500	Style B	Request Info