

Cut-off grinder

GWS 24-300 J + SDS Professional

The specialist tool for extremely deep cuts

- Up to 95 mm cutting depth – for working in steel and stone
- Sturdy cutting guide for exact cutting supplied as standard
- Bow handle at the machine's centre of gravity ensures consistent weight distribution

- Also suitable for dry cutting with diamond disc diameter of up to 300 mm and dust extraction guard
- Comes complete with SDS quick-locking nut
- Handy grip angled to suit the application
- Flat gear head
- Triple-control safety switch with lock function
- Protective guard quick adjustment
- Third securing thread for auxiliary handle, gear housing adjustable by 90° in four directions
- Synthetic resin armored coils for long lifetime of the motor
- Good handling, also for left-handers

Scope of delivery

Part no. 0 601 364 003

- Bow handle (1 607 000 247)
- Hex screw (ET no. 2 603 450 007)
- Protective guard (1 605 510 224)
- Guide (2 608 190 025)
- Backing flange (2 605 703 017)
- Locking flange (2 605 703 016)
- SDS quick-locking nut (1 603 340 031)

Technical data

Rated power input	2.400 W
No-load speed	5.000 rpm
Power output	1.670 W
Grinding spindle thread	M 14
Disc diameter	300 mm
Bore size, diameter	22,2 mm
Weight without cable (EPTA standard)	10,3 kg

Functions

- Starting current limitation