

Drill

GBM 13 HRE Professional

The sturdy, powerful tool

- Highest quality and durability due to cut gears, ball and needle bearings, as well as robust metal gear housing
- Masters simply everything due to the triple reduction gears and the highest torque in its class (60 Nm)
- With the appropriate accessories, even the largest hole diameters, working with hole saws up to 80 mm or stirring thick liquids are no problem



- Control Electronic for exact pilot drilling
- Safe grip with sturdy, long auxiliary handle
- Easy operation with 2-finger pressure switch
- Forward/reverse rotation

Scope of delivery

Part no. 0 601 049 603

- Keyed chuck 13 mm (1 608 571 062)
- Auxiliary handle (1 612 025 020)

Drill chuck, version Keyed chuck

Package (L/W/H) 340 x 250 x 80 mm

Voltage, electrical 230 V

Technical data

Rated power input 550 W

No-load speed 0 – 550 rpm

Power output 285 W

Weight without cable 2,1 kg

Rated speed 380 rpm

Created with

Rated torque 5,0 Nm

Max. torque 60,0 Nm

Drilling range

Drilling dia. in aluminum 20 mm

Drilling dia. in wood 40 mm

Drilling dia. in steel 13 mm

Functions

- Infinitely variable speed control
- Forward/reverse operation
- Electronic