

Drill

GBM 16-2 RE Professional

The perfect tool for formwork drilling

- With spade handle for a firm grip
- Control Electronic for exact pilot drilling
- Forward/reverse rotation specially for loosening jammed formwork drill bits

- Also suitable for stirring
- Synchronized 2-speed draw key transmission; switchover possible during operation
- Spindle collar diameter of 43 mm (European standard) – can be used in drill stands
- Switch operated and locked with one finger
- Long lifetime with roller bearing-mounted motor and gears

Scope of delivery

Part no. 0 601 120 503

- Keyed chuck 16 mm (2 608 571 020)
- Auxiliary handle (ET no. 3 602 025 021)
- Depth stop 310 mm (1 613 001 003)

Drill chuck, version Keyed chuck

Package (L/W/H) 580 x 235 x 100 mm

Voltage, electrical 230 V

Technical data

Rated power input	1.050 W
No-load speed	540 / 1.260 rpm
Power output	570 W
Weight without cable	3,7 kg
Rated speed	380 / 880 rpm
Rated torque	14,0 / 6,0 Nm
Drill spindle connecting thread	Kegel B 16
Max. torque	50,0 / 22,0 Nm

Drilling range

Drilling dia. in aluminum 20 / 13 mm

Drilling dia. in wood 40 / 20 mm

Drilling dia. in steel 16 / 8 mm

Functions

- Multiple gears
- Infinitely variable speed control
- Forward/reverse operation
- Electronic