

## PU-series, economy portable electric pumps



- Lightweight (11,8 to 18,6 kg) and compact design
- Large easy-carry handle for maximum portability
- Two-speed operation reduces cycle times for improved productivity
- 230 VAC 50/60-cycle universal motor (0,37 kW) will operate on poor voltage supply
- 24 VDC remote motor control, 3 m length
- Pump starts under full load
- High strength molded shroud, with integral handle, protects motor from contamination and damage
- This pump is best suited to power small to medium size cylinders or tools, and where easy pump transport is required

For use with cylinders		Pump Speed		Usable Oil Capacity litres	Model Number	Output Flow rate l/min		Valve Type and Function					Weight kg
		Single	Two			1st stage at 13 bar	2nd stage at 700 bar	Man.	Elect.	Adv	Hold	Retr.	
•	-	-	•	1,9	PUD-1100E	3,31	0,32	-	3/2**	•	-	•	11,8
•	-	-	•	3,8	PUD-1101E	3,31	0,32	-	3/2**	•	-	•	17,2
•	-	-	•	1,9	PUJ-1200E	3,31	0,32	3/2	-	•	•	•	10,0
•	-	-	•	3,8	PUJ-1201E	3,31	0,32	3/2	-	•	•	•	15,4
•	-	-	•	1,9	PUD-1300E	3,31	0,32	-	3/2	•	•	•	12,0
•	-	-	•	3,8	PUD-1301E	3,31	0,32	-	3/2	•	•	•	17,5
-	•	-	•	1,9	PUJ-1400E	3,31	0,32	4/3	-	•	•	•	13,2
-	•	-	•	3,8	PUJ-1401E	3,31	0,32	4/3	-	•	•	•	18,6

\* For 115 volt applications change 'E' suffix into 'B'.

\*\* Electric dump valve for auto - retract.