

Flexible Shafts & Accessories - G16 High Speed Flexible Shaft System - G16 High Speed Shaft, Core and Casing

PFERD offers a wealth of possibilities for combining abrasives and power tool systems to achieve the perfect solution for any given material/workpiece and machining task. PFERD power tools include electric, pneumatic and flexible shaft machines. Accessories and tool maintenance equipment for all tools is also available.

PFERD Flexible Shafts are available in a variety of lengths and diameters to suit your needs. Whether you require a large diameter shaft to transfer high torque at low speed, or a highly flexible shaft to run at high speeds with small diameter tools, PFERD offers a wide selection of solutions to equip your flexible shaft machine.

G16 High Speed section includes shafts with a 4mm core diameter for high flexibility and high speed rating (24,000 - 40,000 RPM), and all corresponding handpieces that fit the shaft. Compatible with all PFERD flexible shaft machines available in the U.S. market.

This selection of shafts offers the highest RPM range and the best flexibility. Includes complete assemblies, along with replacement casings and cores



EDP	Description	Core Diameter	Flexible Shaft Length	Overall Assembled Length	Speed Range	Power Range	Max. Bend Radius	
94001	Core and Case Assembled	4 mm	.	4.56'	40,000 - 24,000 RPM	0.67 - 0.4 HP	4"	Request Info
94801	Core Only (Replacement)	4 mm	4.27'	.	40,000 - 24,000 RPM	0.67 - 0.4 HP	4"	Request Info
94501	Case Only (Replacement)	4 mm	4.36'	.	40,000 - 24,000 RPM	0.67 - 0.4 HP	4"	Request Info