

G, H-series, hydraulic pressure gauges



- The visual reference of system pressure

G-series, glycerine filled pressure gauges

- Dual scale reading calibrated in bar and psi
- All pressure sensing parts are sealed and dampened by glycerine for long life
- Safety blow-out disk and pressure equalizing membrane

H-series, high cycle dry pressure gauges

- Dual scale reading calibrated in bar and psi
- Ideal for high cycle applications and harsh environments

Pressure Range		Model Number Glycerine Filled Gauges				Model Nr. Dry Gauges	
		Ø 63 mm 1/4" NPTF Lower Mount Accuracy: ± 1,5 %	Ø 63 mm 1/4" NPTF Center Rear Accuracy: ± 1,5 %	Ø 100 mm 1/4" NPTF Lower Mount Accuracy: ± 1,0 %	Ø 100 mm 1/2" NPTF Lower Mount Accuracy: ± 1,0 %	Ø 100 mm 1/4" NPTF Lower Mount Accuracy: ± 1,0 %	Ø 100 mm 1/2" NPTF Lower Mount Accuracy: ± 1,0 %
0-400	0-6.000	G2517L	G2534R	–	–	–	–
0-700	0-10.000	G2535L	G2537R	G4088L	G4039L	–	–
0-1000	0-15.000	G2536L	G2538R	G4089L	G4040L	–	–
0-700	0-10.000	–	–	–	–	H4049L	H4071L