

MP-series, multifluid hand pumps



- Unbeatable corrosion resistance
- Nitrile seals – for a wide range of fluids such as de-mineralised water, oil/water emulsions, waterglycols, mineral oils
- Two speed pumps up to 1000 bar pressure
- Buna Nitrile seals can be exchanged with optional EPDM seal for use with Skydrol or brake fluids
- Impregnated aluminium anodized pump housing with stainless steel internal pumping components
- Externally adjustable pressure relief valve
- 1/4" NPTF gauge port

For Use With Cylinders		Pump Speed		Pressure Rating		Model Number	Oil Displacement per Stroke		Max. Handle Effort	Piston Stroke	Weight
S/A	D/A	Single	Two	bar			cm ³				
				1st stage	2nd stage		1st stage	2nd stage	kg	mm	kg
•	-	-	•	35	110	MP-110	52,60	21,80	45	26,5	6,6
•	-	-	•	35	350	MP-350	52,60	7,80	45	26,5	6,6
•	-	-	•	35	700	MP-700	52,60	3,10	45	26,5	6,6
•	-	-	•	35	1000	MP-1000	52,60	2,20	45	26,5	6,6

MP-Pumps requires use of external reservoir. Optional 7,4 litres reservoir **MP-10T** available.

Pump includes 1,5 mm gasket for reservoir mounting.