

P-series, lightweight hand pumps



- Lightweight and compact design
- Exclusively from Enerpac
- Durable glass-filled nylon reservoir
- Nylon encapsulated aluminium pump base
- Two-speed operation reduces handle strokes by as much as 78% over single speed pumps
- Integral 4-way valve on P-842 for operation of double-acting cylinders
- Large oil capacities to power a wide variety of cylinders and tools
- Internal pressure relief valve for overload protection

For use with cylinder		Pump Speed		Usable Oil Capacity cm3	Model Number	Pressure Rating**		Oil Displacement per Stroke		Max. Handle Effort kg	Piston Stroke mm	Weight kg
S/A	D/A	Single	Two			bar		cm3				
						1st stage	2nd stage	1st stage	2nd stage			
•	-	•	-	327	P-141	-	700	-	0,90	32,7	12,7	2,0
•	-	•	-	901	P-391	-	700	-	2,47	38,6	25,4	4,1
•	-	-	•	327	P-142*	13	700	3,62	0,90	35,4	12,7	2,0
•	-	-	•	901	P-202	13	700	3,62	0,90	28,6	12,7	3,4
•	-	-	•	901	P-392*	13	700	11,26	2,47	42,2	25,4	4,1
•	-	-	•	2540	P-802	27	700	39,33	2,47	43,1	25,4	8,2
-	•	-	•	2540	P-842	27	700	39,33	2,47	43,1	25,4	10,0

* Available as sets (Cylinder, gauge, couplers, hose and pump)

** Contact Enerpac where operating pressure is less than 10% of pressure rating