




A and C-series, hydraulic couplers



- Quick connection of hydraulic lines
- 700 and 800 bar 1/4" couplers for torque wrenches
- 700 bar 3/8" couplers for cylinders, tools and

Hydraulic Coupler	For use with *	Maximum Pressure bar	Model Number	Thread NPTF	Max. Oil Flow l/min	Model Number	Model Number
			Coupler Complete			Female Half	Male Half
	1	700	C-604	3/8"	35	CR-400	CH-604
	2	700	F-604	3/8"	40	FR-400	FH-604
	3	700	A-604	3/8"	7,6	AR-400	AH-604
	4	700	A-630	1/4"	7,6	AR-630	AH-630
	5	700	T-630	1/4"	11,4	TR-630	TH-630
	6	800	–	1/4"	6,1	CFF-250	CMF-250

* For use with:

1. C-604 High-Flow coupler: most cylinders, tools and pumps
2. F-604 Flush-Face coupler: cylinders and pumps
3. A-604 Regular Spee-D coupler: hand pumps and medium applications
4. A-630 Regular coupler: small cylinders and hand pumps
5. T-630 Spin-on coupler: 700 bar S, W-series wrenches, THQ-series hoses, wrench pumps
6. Lock-ring couplers: 800 bar SQD, HXD-series wrenches, THC-series hoses, wrench pumps.