

SP-series, lightweight hydraulic punch



- Much faster than drilling
- 12,7 mm thick capacity through mild steel
- Round punches and dies are standard
- Optional oblong and square punches and dies
- Long life Enerpac single-acting, spring return design
- Durable steel case keeps tools and dies together and provides for easy carrying and storage
- CR-400 coupler included
- Tool kit SPK-10 included for easy removal and installation of punch into head
- Available as complete set with hand pump, air or electric pump

For higher punch capacity see [50 ton double-acting hydraulic punch](#)

Model Number	Diameter of Punch and Die Set Model Nr. included 1)						Hydraulic set components included				Weight (kg)
	SPD-375	SPD-438	SPD-531	SPD-563	SPD-688	SPD-813	Punch **	Pump	Hose	Gauge + Adaptor GP-10S GA-2	
STP-35H	-	3/8"	-	1/2"	5/8"	3/4"	SP-35	P-392	HC-7206	•	25
STP-35A	-	3/8"	-	1/2"	5/8"	3/4"	SP-35	PATG-1102N	HC-7206	•	29
SP-35	-	-	-	-	-	-	SP-35	-	-	-	16
SP-35S	-	3/8"	-	1/2"	5/8"	3/4"	SP-35	-	-	-	18
SP-35SPE *	-	3/8"	-	1/2"	5/8"	3/4"	SP-35	PUD-1100E	HC-7206	-	29
MSP-351	9,5mm	11,1mm	13,5mm	-	17,5mm	-	SP-35	-	-	-	21
MSP-351PE *	9,5mm	11,1mm	13,5mm	-	17,5mm	-	SP-35	PUD-1100E	HC-7206	-	32

* For 115 Volt electric pump change suffix "E" into "B".

** Oil capacity 76 cm³.

1) Material thickness should not exceed hole diameter.