

## VC, VE, VM-series, 4-way directional control valves



- For reliable control of double-acting cylinders and tools
- Manual or solenoid operation
- Adjustable relief valve on VM and VE-series valves
- All VM and VE-series valves feature several gauge ports for system, A and B port pressure monitoring
- All valves (except VC-series) include manifold with built-in "system check" feature for more precise pressure holding and system control
- VC-series remote valves include Return Line Kit VRL-10

Valve Operation		Valve Location		For use with cylinders / tools	Valve Type	Centre Position			Model Number	Flowpath			Weight kg
Manual	Solenoid	Pump	Remote			D/A	tandem	closed		locking *	advance	hold	
•	-	•	-	•	4/3	•	-	-	<b>VM43</b>	•	•	•	3,1
•	-	•	-	•	4/3	•	-	•	<b>VM43L</b>	•	•	•	4,9
•	-	•	-	•	4/3	•	-	-	<b>VC-4</b>	•	•	•	2,9
•	-	-	•	•	4/3	•	-	•	<b>VC-4L</b>	•	•	•	4,7
•	-	-	•	•	4/3	-	•	-	<b>VC-20</b>	•	•	•	2,9
•	-	-	•	•	4/3	-	•	•	<b>VC-20L</b>	•	•	•	4,7
-	•	•	-	•	4/3	•	-	-	<b>VE43</b>	•	•	•	9,3

\*positive load holding with pilot-operated check valve