

Impact drill

GSB 21-2 RCT Professional

The most powerful tool in its class with Constant Electronic and Torque Control for the toughest applications

- Bosch high-performance motor (1300 W) with high torque for the most heavy-duty applications with large diameters (drilling, working with core cutters and holesaws), screwdriving and stirring
- Constant Electronic for more convenient working: keeps the speed constant, even under load.
- Torque Control for high precision: torque preselection for uniform screwdriving.



- Sturdy metal gear housing for long lifetime
- Anti-rotation mechanical overload clutch for high level of work safety, even in the toughest applications
- Single-sleeve keyless chuck with Auto-Lock for quick accessory changes with only one hand
- New safety handle with innovative attachment and softgrip for a secure hold on the machine
- Rotating brush plate for constant power in reverse and forward rotation
- Softgrip on main handle for a secure hold
- Ball grommet for high movement radius and for preventing cable breaks
- Spindle collar diameter of 43 mm (European standard) – can be used in drill stands

Part no. 0 601 19C 700

- Keyless chuck 13 mm (2 608 572 150)
- Auxiliary handle (2 605 025 193)
- Depth stop 210 mm (1 613 001 010)
- Carrying case (2 605 438 524)

Voltage, electrical 230 V

Technical data

Rated power input	1.300 W
No-load speed	0 – 900 / 3.000 rpm
Power output	695 W
Weight without cable	2,9 kg
Rated speed	900 – 3.000 rpm

Created with

Rated torque	7,8 / 2,6 Nm
Drill spindle connecting thread	1/2" – 20 UNF
Chuck capacity	1,5 – 13 mm
Impact rate at no-load speed	0 – 15.300 / 51.000 bpm
Max. torque	43,0 / 20,5 Nm

Drilling range

Drilling dia. in concrete	22 / 13 mm
Drilling dia. in wood	40 / 25 mm
Drilling dia. in steel	16 / 10 mm
Drilling dia. in masonry	24 / 16 mm

Functions

- Multiple gears
- Forward/reverse operation
- Electronic
- Constant Electronic
- Power Control
- Auto-Lock
- Softgrip
- Overload clutch