



Knot Wheels, Threaded - COMBITWIST® - Standard Twist - Carbon Steel

Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

For maximum performance knot wheel brushes, COMBITWIST knot design offers market-leading performance. Conventional knot wheel brushes are manufactured with all knots twisted in one direction. Innovative COMBITWIST brushes are produced with alternating left hand - right hand knots. This unique knot configuration yields many benefits to improve your efficiency, and lower your overall costs:

- More aggressive brushing action
- Longer brush life
- Superior rotational balance
- Faster stock removal and better finish
- Easier control with less operator fatigue

COMBITWIST wheel brushes in standard twist offer aggressive brushing action with superior results when compared to conventional knot wheel brushes. This section includes all threaded standard twist knot wheels featuring COMBITWIST technology in Carbon Steel wire.



EDP Brush Diameter Thread Size Wire Size Trim Length Face Width Max. RPM

82383	4	5/8-11	.014	7/8	5/8	20,000	Request Info
82384	4	5/8-11	.020	7/8	5/8	20,000	Request Info
82680	5	5/8-11	.020	5/8	5/8	15,000	Request Info
82681	6	5/8-11	.014	1-1/8	5/8	9,000	Request Info
82682	6	5/8-11	.016	1-1/8	5/8	9,000	Request Info
82683	6	5/8-11	.023	1-1/8	5/8	9,000	Request Info