



Knot Wheels, Threaded - COMBITWIST® - Standard Twist - Stainless Steel

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

For maximum performance knot wheel brushes, COMBITWIST knot design offers market-leading performance. Conventional knot wheel brushes are manufactured with all knots twisted in one direction. Innovative COMBITWIST brushes are produced with alternating left hand - right hand knots. This unique knot configuration yields many benefits to improve your efficiency, and lower your overall costs:

- More aggressive brushing action
- Longer brush life
- Superior rotational balance
- Faster stock removal and better finish
- Easier control with less operator fatigue

COMBITWIST wheel brushes in standard twist offer aggressive brushing action with superior results when compared to conventional knot wheel brushes. This section includes all threaded standard twist knot wheels featuring COMBITWIST technology in Stainless Steel wire.



EDP	Brush Diameter	Thread Size	Wire Size	Trim Length	Face Width	Max. RPM	
-----	----------------	-------------	-----------	-------------	------------	----------	--

82413	4	5/8-11	.020	7/8	5/8	20,000	Request Info
-------	---	--------	------	-----	-----	--------	------------------------------

82749	5	5/8-11	.020	5/8	5/8	15,000	Request Info
-------	---	--------	------	-----	-----	--------	------------------------------

82752	6	5/8-11	.016	1-1/8	5/8	9,000	Request Info
-------	---	--------	------	-------	-----	-------	------------------------------

82753	6	5/8-11	.023	1-1/8	5/8	9,000	Request Info
-------	---	--------	------	-------	-----	-------	------------------------------