



## Knot Wheels, Threaded - Standard Twist - Stainless Steel Wire

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

Standard twist knots are twisted for approximately 75% of the length of the knot. They offer faster removal rates than crimped wire wheel brushes, with a more aggressive brushing action.



EDP	Brush Diameter	Thread Size	Wire Size	Trim Length	Face Width	Max. RPM	
82283 4		5/8-11	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82279 3		M10x1.25	.014	5/8	7/16	25,000	<a href="#">Request Info</a>
82280 3		3/8-24	.014	5/8	7/16	25,000	<a href="#">Request Info</a>
82596 5		5/8-11	.020	5/8	5/8	15,000	<a href="#">Request Info</a>
82597 6		5/8-11	.016	1-1/8	5/8	9,000	<a href="#">Request Info</a>
82284 4		5/8-11	.020	7/8	5/8	20,000	<a href="#">Request Info</a>
82598 6		5/8-11	.023	1-1/8	5/8	9,000	<a href="#">Request Info</a>
82285 4		1/2-13	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82286 4		1/2-13	.020	7/8	5/8	20,000	<a href="#">Request Info</a>
82287 4		3/8-24	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82288 4		3/8-24	.020	7/8	5/8	20,000	<a href="#">Request Info</a>
82289 4		M10x1.50	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82290 4		M10x1.50	.020	7/8	5/8	20,000	<a href="#">Request Info</a>
82291 4		M10x1.25	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82292 4		M10x1.25	.020	7/8	5/8	20,000	<a href="#">Request Info</a>
82293 4		M14x2.0	.014	7/8	5/8	20,000	<a href="#">Request Info</a>
82294 4		M14x2.0	.020	7/8	5/8	20,000	<a href="#">Request Info</a>