



Knot Wheels, Threaded - Stringer Bead Twist - COMBITWIST - Carbon Steel Wire

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

Stringer Bead knot wheel brushes are manufactured with tightly twisted knots and narrow face widths. Designed for tough applications, such as cleaning welds between passes when joining pipe. Stringer bead knots are characterized by low flex, high impact brushing.



EDP	Brush Diameter	Thread Size	Wire Size	No. of Knots	Trim Length	Face Width	Max. RPM	
82391	4	5/8-11	.020	32	3/4	3/16	20,000	Request Info
82392	4-1/2	5/8-11	.020	32	1	3/16	20,000	Request Info
82689	4-7/8	5/8-11	.020	48	3/4	3/16	15,000	Request Info
82690	4-7/8	M14x2.0	.020	48	3/4	3/16	15,000	Request Info
82692	6	5/8-11	.020	40	1-1/8	3/16	12,500	Request Info
82693	6	5/8-11	.020	48	1-1/8	3/16	12,500	Request Info
82694	6	5/8-11	.020	56	1-1/8	3/16	12,500	Request Info
82695	6	5/8-11	.020	64	1-1/8	1/8	12,500	Request Info
82700	6-7/8	5/8-11	.020	56	1-1/8	3/16	9,000	Request Info
82701	6-7/8	5/8-11	.020	72	1-1/8	3/16	9,000	Request Info