



Knot Wheels, Threaded - Stringer Bead Twist - COMBITWIST - Stainless Steel Wire

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

Stringer Bead knot wheel brushes are manufactured with tightly twisted knots and narrow face widths. Designed for tough applications, such as cleaning welds between passes when joining pipe. Stringer bead knots are characterized by low flex, high impact brushing.



EDP	Brush Diameter	Thread Size	Wire Size	No. of Knots	Trim Length	Face Width	Max. RPM	
82759	4-7/8	5/8-11	.020	48	3/4	3/16	15,000	Request Info
82420	4	5/8-11	.020	32	3/4	3/16	20,000	Request Info
82760	4-7/8	M14x2.0	.020	48	3/4	3/16	15,000	Request Info
82421	4-1/2	5/8-11	.020	32	1	3/16	20,000	Request Info
82762	6	5/8-11	.020	40	1-1/8	3/16	12,500	Request Info
82763	6	5/8-11	.020	48	1-1/8	3/16	12,500	Request Info
82764	6	5/8-11	.020	56	1-1/8	3/16	12,500	Request Info
82765	6	5/8-11	.020	64	1-1/8	1/8	12,500	Request Info
82770	6-7/8	5/8-11	.020	56	1-1/8	3/16	9,000	Request Info
82771	6-7/8	5/8-11	.020	72	1-1/8	3/16	9,000	