



Knot Wheels, Threaded - Stringer Bead Twist - Carbon Steel Wire

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

Stringer Bead knot wheel brushes are manufactured with tightly twisted knots and narrow face widths. Designed for tough applications, such as cleaning welds between passes when joining pipe. Stringer bead knots are characterized by low flex, high impact brushing.

This selection of Stringer Bead brushes includes diameters ranging from 4-7/8" through 6-7/8" manufactured with Carbon Steel Wire.

Advance Brush also offers a wide selection of 4" diameter brushes for use on Mini Grinders in a wide a selection of thread sizes to match your tool.



EDP	Brush Diameter	Thread Size	Wire Size	No. of Knots	Trim Length	Face Width	Max. RPM	
82194	4-1/2	5/8-11	.020	32	1	3/16	20,000	Request Info
82479	4-7/8	5/8-11	.020	38	3/4	3/16	15,000	Request Info
82480	4-7/8	7/8 A.H.	.020	48	3/4	3/16	15,000	Request Info
82481	4-7/8	M14x2.0	.020	38	3/4	3/16	15,000	Request Info
82483	4-7/8	5/8-11	.020	48	3/4	3/16	15,000	Request Info
82484	4-7/8	M14x2.0	.020	48	3/4	3/16	15,000	Request Info
82486	6	5/8-11	.020	40	1-1/8	3/16	12,500	Request Info
82487	6	5/8-11	.020	48	1-1/8	3/16	12,500	Request Info
82488	6	5/8-11	.020	56	1-1/8	3/16	12,500	Request Info
82489	6	5/8-11	.020	64	1-1/8	1/8	12,500	Request Info
82490	6	M14x2.0	.020	56	1-1/8	3/16	12,500	Request Info
82491	6	7/8" A.H.	.020	56	1-1/8	3/16	12,500	Request Info
82494	6-7/8	5/8-11	.020	56	1-1/8	3/16	9,000	Request Info
82495	6-7/8	5/8-11	.020	72	1-1/8	1/8	9,000	Request Info
82497	6-7/8	M14x2.0	.020	56	1-1/8	3/16	9,000	Request Info
82498	6-7/8	M14x2.0	.020	72	1-1/8	3/16	9,000	Request Info
82499	6-7/8	7/8" A.H.	.020	72	1-1/8	3/16	9,000	Request Info