



## Knot Wheels, Threaded - Stringer Bead Twist - Stainless Steel Wire

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

These Advance wheel brushes are manufactured with threaded arbor holes for easy mounting and unmounting on threaded shaft power tools.

Stringer Bead knot wheel brushes are manufactured with tightly twisted knots and narrow face widths. Designed for tough applications, such as cleaning welds between passes when joining pipe. Stringer bead knots are characterized by low flex, high impact brushing.

In addition to this range of larger diameter Stringer Bead brushes listed below, Advance Brush also offers a wide selection of 4" diameter brushes for use on Mini Grinders in a wide a selection of thread sizes to match your tool.



EDP	Brush Diameter	Thread Size	Wire Size	No. of Knots	Trim Length	Face Width	Max. RPM	
82315	4-1/2	5/8-11	.020	32	1	3/16	20,000	<a href="#">Request Info</a>
82604	4-7/8	5/8-11	.020	38	3/4	3/16	15,000	<a href="#">Request Info</a>
82605	4-7/8	7/8 A.H.	.020	48	3/4	3/16	15,000	<a href="#">Request Info</a>
82606	4-7/8	M14x2.0	.020	38	3/4	3/16	15,000	<a href="#">Request Info</a>
82608	4-7/8	5/8-11	.020	48	3/4	3/16	15,000	<a href="#">Request Info</a>
82609	4-7/8	M14x2.0	.020	48	3/4	3/16	15,000	<a href="#">Request Info</a>
82611	6	5/8-11	.020	40	1-1/8	3/16	12,500	<a href="#">Request Info</a>
82612	6	5/8-11	.020	48	1-1/8	3/16	12,500	<a href="#">Request Info</a>
82613	6	5/8-11	.020	56	1-1/8	3/16	12,500	<a href="#">Request Info</a>
82614	6	5/8-11	.020	64	1-1/8	1/8	12,500	<a href="#">Request Info</a>
82619	6-7/8	5/8-11	.020	56	1-1/8	3/16	9,000	<a href="#">Request Info</a>
82620	6-7/8	5/8-11	.020	72	1-1/8	1/8	9,000	<a href="#">Request Info</a>