



Knot Wheels, Unthreaded - Standard Twist -Heavy Duty Double Row

ADVANCE BRUSH offers a complete range power brushes for Industrial use, including Wheel, End, Cup, Shaft Mount, and Tube brushes. Featuring M-BRAD™ Nylon Abrasive filament wheels, cup, disc brushes and more.

Advance unthreaded knot wheels are available in a variety of twist-types and knot configurations. Ranging from 3" to 16" in diameter, selection includes standard twist single and double row brushes for aggressive brushing action, as well as specialty brushes like short trim wheel for high impact, heavy duty use, and long trim for a less aggressive brushing action and improved surface finish. Includes pipe cleaning and joint expansion brushes.

Double row knot wire wheel brushes are commonly used for deflashing and cleaning of insert molded rubber parts, removing heavy surface contamination, and heavy deburring of machined parts.



EDP	Brush Diameter	Arbor Hole	Wire Size	Trim Length	Face Width	Max. RPM	
82030	3	1/2-3/8	.012	3/4	3/4	20,000	Request Info
82031	3	1/2-3/8	.020	3/4	3/4	20,000	Request Info
82032	4	5/8-1/2	.014	3/4	1	20,000	Request Info
82033	6	2	.012	1-1/8	1	7,800	Request Info
82034	6	2	.016	1-1/8	1	7,800	Request Info
82035	8	2	.012	1-5/8	1-1/8	6,000	Request Info
82036	8	2	.016	1-5/8	1-1/8	6,000	Request Info
82037	8	2	.023	1-5/8	1-1/8	6,000	Request Info
82038	10	2	.012	2-1/8	1-1/4	4,800	Request Info
82039	10	2	.01	2-1/8	1-1/4	4,800	Request Info
82040	10	2	.023	2-1/8	1-1/4	4,800	Request Info
82041	12	2	.012	2	1-5/8	4,000	Request Info
82042	12	2	.016	2	1-5/8	4,000	Request Info
82043	12	2	.023	2	1-5/8	4,000	Request Info