

ZW-series, Z-Class electric workholding pumps

Z-Class high efficiency single-stage pumps

Pallet de-coupling pumps



- Provides momentary pressure and flow to fixture
- Ideal for pallet disconnect systems

Continuous connection pumps

- Provides solenoid control of one single- or double-acting circuit
- Includes pilot operated check valve ensuring pressure is maintained in circuit

Single station DO3 pumps

- Industry standard mounting for manual or electric valves
- Options: backlit LCD, heat exchanger, pressure transducer, level & temperature switches and roll bars

SAE Ported for Remote Valves

- 10mm tube elbows supplied in manifold

Output Flow at 350 bar	Motor Size	Motor Voltage	Usable Oil Capacity	Pallet De-coupling Pumps	Continuous Connection Pumps	Single Station DO3 Pumps	SAE Ported for Remote Valving	Weight
l/min	kw	Volt-phase at 50Hz	liters	Model Number	Model Number	Model Number	Model Number	kg
0,54	0,75	115-1	8	ZW3408DB-FT	ZW3408FB-FT		ZW3008HB-FT01	53
0,54	0,75	115-1	10	ZW3410DB-FT	ZW3410FB-FT		ZW3010HB-FT01	61
0,54	0,75	230-1	8	ZW3408DE-FT	ZW3408FE-FT		ZW3008HE-FT01	53
0,54	0,75	230-1	10	ZW3410DE-FT	ZW3410FE-FT		ZW3010HE-FT01	61
0,82	0,75	115-1	10	ZW4410DB-FT	ZW4410FB-FT	ZW4410GB-11	ZW4010HB-FT01	68
0,82	0,75	400-3	10	ZW4410DW-FT	ZW4410FW-FT	ZW4410GW-11	ZW4010HW-FT01	68
1,64	1,12	115-1	10	ZW5410DB-FT	ZW5410FB-FT	ZW5410GB-11	ZW5010HB-FT01	72
1,64	1,12	400-3	10	ZW5410DW-FT	ZW5410FW-FT	ZW5410GW-FT	ZW5410HW-FT01	72