

Pressure Washers

Compact mobile cold water

POSEIDON 2



Compact cold water power

The compact cold water line that combines high performance level for increased cleaning efficiency, ergonomics and durability for superior everyday cleaning.

Product facts

- Ergonomic and compact design
- Ergo 1000 accessory concept
- XT model with hose reel, additional hose and rotary jet lance.
- Detergent injector hose and doser

Technical data

| | | |
|--|---------------|---------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 2,8 | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 600/570 | 600/570 |
| MAX INLET TEMPERATURE (°C) | 60 | 60 |
| NUMBER OF PISTONS | 3 | 3 |
| CERAMIC PISTONS | X | X |
| PUMP (RPM) | 2800 | 2800 |
| DIMENSIONS LXWXH (MM) | 394X391X955 | 394X391X955 |
| WEIGHT (KG) | 23,5 | 23,5 |
| POWER CONSUMPTION (KW) | 3,3 | 3,3 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/14,5 | 230/1/50/14,5 |
| EL CABLE (M) | 5 | 5 |
| DETERGENT TANK (L) | 2,5 | 2,5 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0350 | 0350 |

Poseidon 2-28

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 600/570 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 2800 |
| DIMENSIONS LXWXH (MM) | 394X391X955 |
| WEIGHT (KG) | 23,5 |
| POWER CONSUMPTION (KW) | 3,3 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/14,5 |
| EL CABLE (M) | 5 |
| DETERGENT TANK (L) | 2,5 |
| AUTO STANDBY | X |
| NOZZLE SIZE | 0350 |

Poseidon 2-28 XT

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 600/570 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 2800 |
| DIMENSIONS LXWXH (MM) | 394X391X955 |
| WEIGHT (KG) | 23,5 |
| POWER CONSUMPTION (KW) | 3,3 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/14,5 |
| EL CABLE (M) | 5 |
| DETERGENT TANK (L) | 2,5 |
| AUTO STANDBY | X |
| NOZZLE SIZE | 0350 |

Compact mobile cold water

POSEIDON 2 PORTABLE



Portable cold water power

The compact cold water line that combines high performance level for increased cleaning efficiency, ergonomics and durability for superior everyday cleaning.

Product facts

- Compact design.
- Steel protective bar.
- Ceramic pistons.
- Ergo 1000 accessory concept.

| Technical data | Poseidon 2-24 Port | Poseidon 2-26 Port |
|--|--------------------|--------------------|
| PUMP PRESSURE (BAR/MPA) | 100/10 | 140/14 |
| CLEANING IMPACT (KG/FORCE) | 2,4 | 2,6 |
| WATER FLOW QMAX/QIEC (L/H) | 650/600 | 610/540 |
| MAX INLET TEMPERATURE (°C) | 40 | 40 |
| NUMBER OF PISTONS | 3 | 3 |
| PUMP (RPM) | 2800 | 2800 |
| DIMENSIONS LXWXH (MM) | 555X290X275 | 555X290X275 |
| WEIGHT (KG) | 24 | 24 |
| POWER CONSUMPTION (KW) | 2,2 | 3,2 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/10 | 230/1/50/14 |
| EL CABLE (M) | 5 | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 | 0,5 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0500 | 0350 |

Compact mobile cold water

POSEIDON 3



The right machine for semi-professional, everyday use

The new semi-professional cold water line combining high performance level for increased cleaning efficiency, ergonomic design and robustness for superior everyday cleaning. Models designed for everyday use by tradesmen, on small construction sites, hobby and milk farms or in rental.

Product facts

- Ergonomic and compact design.
- Detergent injector hose and doser.
- XT model with hose reel, additional hose and rotary jet lance.
- Ergo accessory concept.

| Technical data | Poseidon 3-40 | Poseidon 3-40 XT | Poseidon 3-30 | Poseidon 3-30 XT |
|--|---------------|------------------|---------------|------------------|
| PUMP PRESSURE (BAR/MPA) | 170/17 | 170/17 | 150/15 | 150/15 |
| CLEANING IMPACT (KG/FORCE) | 4,0 | 4,0 | 3,0 | 3,0 |
| WATER FLOW QMAX/QIEC (L/H) | 825/750 | 825/750 | 660/600 | 660/600 |
| MAX INLET TEMPERATURE (°C) | 60 | 60 | 60 | 60 |
| NUMBER OF PISTONS | 3 | 3 | 3 | 3 |
| STAINLESS STEEL PISTONS | X | X | X | X |
| PUMP (RPM) | 2800 | 2800 | 2800 | 2800 |
| DIMENSIONS LXWXH (MM) | 1020X400X400 | 1020X400X400 | 1020X400X400 | 1020X400X400 |
| WEIGHT (KG) | 35 | 37,5 | 34,5 | 37 |
| POWER CONSUMPTION (KW) | 4,2 | 4,2 | 3,4 | 3,4 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/8,5 | 400/3/50/8,5 | 230/1/50/16 | 230/1/50/16 |
| SUCTION HEIGHT DRY (M) | 0,5 | 0,5 | 0,5 | 0,5 |
| NOZZLE SIZE | 0450 | 0450 | 0400 | 0400 |

Compact mobile cold water

POSEIDON 4



Compact cold water power

The new POSEIDON 4 is a robust and durable addition to our low mid range line of cold water pressure washers. Ideal for small and medium sized agricultural sites or for craftsmen and trade. The machine is powered by a tough and efficient 1450 RPM motor giving long lifetime and high reliability.

Product facts

- 1450 RPM pump.
- 3 ceramic pistons.
- 4 L detergent tank.
- Ergonomic design

Technical data

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 140/14 |
| CLEANING IMPACT (KG/FORCE) | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 620/580 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 3,1 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/13 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE (TORNADO PLUS) | 0400 |

Poseidon 4-28

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 140/14 |
| CLEANING IMPACT (KG/FORCE) | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 620/580 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 3,1 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/13 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE (TORNADO PLUS) | 0400 |

Poseidon 4-28 XT

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 140/14 |
| CLEANING IMPACT (KG/FORCE) | 2,8 |
| WATER FLOW QMAX/QIEC (L/H) | 620/580 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 3,1 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/13 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE (TORNADO PLUS) | 0400 |

Poseidon 4-30

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 170/17 |
| CLEANING IMPACT (KG/FORCE) | 3,0 |
| WATER FLOW QMAX/QIEC (L/H) | 620/560 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 3,8 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/16 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE (TORNADO PLUS) | 0340 |

Poseidon 4-30 XT

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 170/17 |
| CLEANING IMPACT (KG/FORCE) | 3,0 |
| WATER FLOW QMAX/QIEC (L/H) | 620/560 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 3,8 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/16 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE (TORNADO PLUS) | 0340 |

Technical data

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 760/700 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 4,4 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/7,3 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE | 0435 |

Poseidon 4-36

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 760/700 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 4,4 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/7,3 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE | 0435 |

Poseidon 4-36 XT

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 760/700 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 4,4 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/7,3 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE | 0435 |

Poseidon 4-41

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 4,1 |
| WATER FLOW QMAX/QIEC (L/H) | 780/840 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 5,0 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/8,5 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE | 0435 |

Poseidon 4-41 XT

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 4,1 |
| WATER FLOW QMAX/QIEC (L/H) | 780/840 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP | 1450 RPM |
| DIMENSIONS LXWXH (MM) | 400X400X1030 |
| DETERGENT TANK (L) | 4 |
| WEIGHT (KG) | 45 |
| POWER CONSUMPTION (KW) | 5,0 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/8,5 |
| EL CABLE (M) | 5 |
| SUCTION HEIGHT DRY (M) | 0,5 |
| NOZZLE SIZE | 0435 |

Medium mobile cold water

POSEIDON 5



Performance, ergonomics and durability

The ideal partner for cold water cleaning tasks in all sectors. High performance, unbeatable ergonomics, low noise levels and easy servicing make this an unmatched pressure washer.

Product facts

- 1450 rpm motor pump units.
- 50% reduction in noise level.
- All controls in one place for ease of use.
- Visible oil level.
- Hose reel, additional hose, rotary nozzle lance and detergent tank on XT models.
- Full ceramic piston sleeves.

| Technical data | POSEIDON 5-55 | | | POSEIDON 5-61 | | |
|--|------------------------|----------|--|---------------|------|----------|
| EL CABLE (M) | | 5 | | | 7 | 5 |
| POWER CONSUMPTION (KW) | 6,4 | | | | | |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400-230/3/50/19,8-11,9 | | | 400/3/50/12,6 | | |
| CLEANING IMPACT (KG/FORCE) | 5,5 | | | 6,1 | | |
| WATER FLOW QMAX/QIEC (L/H) | 1050/970 | | | 1130/1040 | | |
| PUMP PRESSURE (BAR/MPA) | | 205/20,5 | | | 1450 | 215/21,5 |
| PUMP (RPM) | 1450 | | | | | |
| PUMP | | NA5 | | | 1450 | NA5 |
| DETERGENT TANK (L) | 6 | | | 6 | | |
| NOZZLE SIZE | | 0500 | | | | 530 |
| MAX INLET TEMPERATURE (°C) | 60 | | | 60 | | |
| NUMBER OF PISTONS | 3 | | | 3 | | |
| CERAMIC PISTONS | | X | | | X | |
| DIMENSIONS LXWXH (MM) | 740x550x1015 | | | 740x550x1015 | | |
| SUCTION HEIGHT DRY (M) | 1,5 | | | 1,5 | | |
| WEIGHT (KG) | | 75 | | | | 79 |

| Technical data | Poseidon 5-28 | Poseidon 5-28 XT | Poseidon 5-43 | Poseidon 5-54 | Poseidon 5-54 XT | Poseidon 5-62 | Poseidon 5-62XT | Poseidon 5-63 | Poseidon 5-63 XT |
|--|---------------|------------------|---------------|---------------|------------------|---------------|-----------------|---------------|------------------|
| PUMP PRESSURE (BAR/MPA) | 110/11 | 110/11 | 180/18 | 200/20 | 200/20 | 220/22 | 220/22 | 170/17 | 170/17 |
| CLEANING IMPACT (KG/FORCE) | 2,8 | 2,8 | 4,3 | 5,4 | 5,4 | 6,2 | 6,2 | 6,3 | 6,3 |
| WATER FLOW QMAX/QIEC (L/H) | 720/660 | 720/660 | 860/800 | 1030/950 | 1030/950 | 1130/1050 | 1130/1050 | 1300/1200 | 1300/1200 |
| MAX INLET TEMPERATURE (°C) | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| NUMBER OF PISTONS | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| CERAMIC PISTONS | X | X | X | X | X | X | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 |
| DIMENSIONS LXWXH (MM) | 740X550X1015 | 920X550X1015 | 740X570X1015 | 740X550X1015 | 920X550X1015 | 740X570X1015 | 920X550X1015 | 740X570X1015 | 920X550X1015 |
| WEIGHT (KG) | 70 | 80 | 70 | 75 | 85 | 79 | 89 | 79 | 89 |
| POWER CONSUMPTION (KW) | 3 | 3 | 5,3 | 6,3 | 6,3 | 7,8 | 7,8 | 7,8 | 7,8 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/13 | 230/1/50/13 | 400/3/50/9,2 | 400/3/50/12,3 | 400/3/50/12,3 | 400/3/50/14,1 | 400/3/50/14,1 | 400/3/50/14,1 | 400/3/50/14,1 |
| EL CABLE (M) | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| DETERGENT TANK (L) | | 7 | 7 | | | 7 | | 7 | 7 |
| SUCTION HEIGHT DRY (M) | 1,5 | 1,5 | 1,5 | 1,5 | 1,5 | 1,5 | 1,5 | 1,5 | 1,5 |
| NOZZLE SIZE | 0500 | 0500 | 0500 | 0530 | 0550 | 0550 | 0550 | 0750 | 0750 |

Premium mobile cold water

POSEIDON 7



Power, robustness and durability

The ultimate industrial cold water unit with high water flow and high pressure. Ideal for agriculture, industry or food industry.

Product facts

- Heavy duty C3 pumps with extended lifetime.
- Inlet temperature up to 85°C.
- Ergo 3000 spray gun for unmatched user comfort.
- 1450 rpm motor.
- Ceramic pistons.
- Stainless steel frame, grey wheel and hoses on POSEIDON 7-66 F/FB.

| Technical data | Poseidon 7-59 | Poseidon 7-66 F | Poseidon 7-66 | Poseidon 7-66 FB |
|-------------------------|---------------|-----------------|---------------|------------------|
| PUMP PRESSURE (BAR/MPA) | 170/17 | 190/19 | 190/19 | 190/19 |

| | | | | |
|--|--------------|--------------|--------------|--------------|
| CLEANING IMPACT (KG/FORCE) | 5,9 | 6,6 | 6,6 | 6,6 |
| WATER FLOW QMAX/QIEC (L/H) | 1200/1120 | 1280/1180 | 1280/1180 | 1280/1180 |
| MAX INLET TEMPERATURE (°C) | 85 | 85 | 85 | 70 |
| NUMBER OF PISTONS | 4 | 4 | 4 | 4 |
| CERAMIC PISTONS | X | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 |
| DIMENSIONS LXWXH (MM) | 1020X480X940 | 1020X480X940 | 1020X480X940 | 1020X480X940 |
| WEIGHT (KG) | 71 | 74 | 74 | 74 |
| POWER CONSUMPTION (KW) | 7,1 | 8 | 8 | 8 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/12 | 400/3/50/14 | 400/3/50/14 | 400/3/50/14 |
| EL CABLE (M) | 8 | 8 | 8 | 8 |
| NOZZLE SIZE | 0640 | 0640 | 0640 | 0640 |

Premium mobile cold water

POSEIDON 8

New premium class high flow cold water line

The new POSEIDON 8 line offers a wide range of models for everyday cleaning in agriculture, construction, and food or transport industry. The POSEIDON 8 offers powerful cleaning, low noise level and high durability.

Product facts

- Steel or stainless steel frame variants.
- Slow running 1450 rpm motors with low noise level.
- Ceramic pistons for longer working life.
- Simple and easy to use.
- Soft start system.
- Stainless steel frame on ST versions.



Technical data

| | |
|--|-------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 11,1 |
| WATER FLOW QMAX/QIEC (L/H) | 2100/2050 |
| MAX INLET TEMPERATURE (°C) | 50 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| DIMENSIONS LXWXH (MM) | 900X910X660 |
| WEIGHT (KG) | 98 |
| POWER CONSUMPTION (KW) | 14 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24 |
| NOZZLE SIZE | 1200 |

Poseidon 8-111

| | |
|--|-------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 11,1 |
| WATER FLOW QMAX/QIEC (L/H) | 2100/2050 |
| MAX INLET TEMPERATURE (°C) | 50 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| DIMENSIONS LXWXH (MM) | 900X910X660 |
| WEIGHT (KG) | 98 |
| POWER CONSUMPTION (KW) | 14 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24 |
| NOZZLE SIZE | 1200 |

Poseidon 8-111 ST

| | |
|--|-------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 11,1 |
| WATER FLOW QMAX/QIEC (L/H) | 2100/2050 |
| MAX INLET TEMPERATURE (°C) | 50 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| DIMENSIONS LXWXH (MM) | 900X910X660 |
| WEIGHT (KG) | 97 |
| POWER CONSUMPTION (KW) | 14 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24 |
| NOZZLE SIZE | 1200 |

Poseidon 8-125

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 12,5 |
| WATER FLOW QMAX/QIEC (L/H) | 2500/2450 |
| MAX INLET TEMPERATURE (°C) | 50 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| DIMENSIONS LXWXH (MM) | 900X910X660 |
| WEIGHT (KG) | 98 |
| POWER CONSUMPTION (KW) | 14 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24,9 |
| NOZZLE SIZE | 1590 |

Poseidon 8-125 ST

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 12,5 |
| WATER FLOW QMAX/QIEC (L/H) | 2500/2450 |
| MAX INLET TEMPERATURE (°C) | 50 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| DIMENSIONS LXWXH (MM) | 900X910X660 |
| WEIGHT (KG) | 97 |
| POWER CONSUMPTION (KW) | 14 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24,9 |
| NOZZLE SIZE | 1590 |

Pressure washers - Petrol driven

POSEIDON PE/DE

Petrol and diesel driven pressure washers - Power, autonomy, and robustness

When electrical power is not available, the heavy duty POSEIDON PE and DE offer autonomy and excellent cleaning power in one tough and robust steel chassis design. Self-priming and suction capability allows you to draw water from a well, tank, lake or other natural source.

Product facts

- Robust long life pumps with ceramic pistons.
- Robust design.
- Honda motor on petrol versions.
- Wide range of models for all applications.
- Ergo accessory concept.



| Technical data | Poseidon 2-31Pe | Poseidon 3-36Pe | Poseidon 5-47Pe | Poseidon 5-53Pe | Poseidon 5-67Pe | Poseidon 5-54 de |
|----------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|
| PUMP PRESSURE (BAR/MPA) | 140 | 140 | 190 | 200 | 230 | 195 |
| CLEANING IMPACT (KG/FORCE) | 3,1 | 3,6 | 4,7 | 5,3 | 6,7 | 5,4 |
| WATER FLOW QMAX/QIEC (L/H) | 700/650 | 840/750 | 900/840 | 1030/930 | 1150/1100 | 1000/950 |
| MAX INLET TEMPERATURE (°C) | 60 | 60 | 60 | 60 | 70 | 60 |
| NUMBER OF PISTONS | 3 | 3 | 3 | 3 | 3 | 3 |
| CERAMIC PISTONS | X | X | X | X | X | X |
| PUMP (RPM) | 3400 | 3400 | 3400 | 3400 | 1550 | 1500 |
| POWER SOURCE DIESEL | | | | | | X |
| POWER SOURCE PETROL | X | X | X | X | X | |
| DIMENSIONS LXWXH (MM) | 800X565X1010 | 800X565X1010 | 800X565X1010 | 800X565X1010 | 800X565X1010 | 1000X615X1150 |
| SUCTION HEIGHT DRY (M) | 0,5 | 0,5 | 0,5 | 0,5 | 0,5 | 0,5 |
| NOZZLE SIZE | 0400 | 0500 | 0450 | 0500 | 0550 | 0530 |
| SPEED (RPM) | 3400/3400 | 3400/3400 | 3400/3400 | 3400/3400 | 3400/1550 | 3400/1500 |

Pressure washers - Petrol driven KLU/KOS



Pneumatic and hydraulic powered pressure washers

Pneumatic and hydraulic powered pressure washers are ideal for potentially dangerous zones where diesel or electrical power is not recommended.

Product facts

- 4 piston pump.

| Technical data | 4403 KOS | 44c3 KOS | 2603Klu |
|----------------------------|--------------------------|--------------------------|--------------|
| PUMP PRESSURE (BAR/MPA) | 160 | 160 | 120 |
| CLEANING IMPACT (KG/FORCE) | 5,9 | 5,9 | 3,9 |
| WATER FLOW QMAX/QIEC (L/H) | 1150/1040 | 1150/1040 | 950/880 |
| MAX INLET TEMPERATURE (°C) | 65 | 65 | 40 |
| NUMBER OF PISTONS | 4 | 4 | 4 |
| STAINLESS STEEL PISTONS | X | | X |
| POWER SOURCE PNEUMATIC | | | X |
| POWER SOURCE HYDRAULIC | X | X | |
| DIMENSIONS LXWXH (MM) | 530X319X450 | 530X319X450 | 1000X545X825 |
| WEIGHT (KG) | 44 | 44 | 70 |
| POWER CONSUMPTION (KW) | FLUID DRIVEN 2,7L 95 BAR | FLUID DRIVEN 2,7L 95 BAR | 170M3/H |
| NOZZLE SIZE | 0640 | 0640 | 0640 |

| | | | | | | | | |
|--|---------------|---------------|--------------|--------------|---------------|--------------|--------------|---------------|
| CERAMIC PISTONS | X | X | X | X | X | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 | 1450 | 14 | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 80/140 | 80/140 | 80/140 | 80/140 | 80/140 | 80/14 | | 80/140 80/140 |
| FUEL CONSUMPTION DT 45 °C (KG/H) | 3,5 | 3,5 | 4,1 | 4,1 | 4,4 | 4, | 4,9 | 4,9 |
| FUEL TANK (L) | 15 | 15 | 15 | 15 | 15 | 1 | 15 | 15 |
| DIMENSIONS LxWxH (MM) | 1053X685X760 | 1053X685X760 | 1053X685X760 | 1053X685X760 | 1053X685X760 | 1053X685X76 | 1053X685X760 | 1053X685X760 |
| WEIGHT (KG) | 135 | 140 | 135 | 140 | 135 | 14 | 135 | 140 |
| POWER CONSUMPTION (KW) | 3,4 | 3,4 | 5,6 | 5,6 | 6,9 | 6, | | 7,9 7,9 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/15,6 | 230/1/50/15,6 | 400/3/50/10 | 400/3/50/10 | 400/3/50/12,5 | 400/3/50/12, | 400/3/50/14 | 400/3/50/14 |
| EL. CABLE (M) | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| NOZZLE SIZE | 0530 | 0550 | 0475 | 0475 | 0550 | 0550 | 0500 | 0500 |

Medium mobile hot water

NEPTUNE 5



The professional solution

The versatile Neptune 5 series combines low running costs, ease of use, low noise and high cleaning efficiency. The most effective tool for daily hot water cleaning in any sector.

Product facts

- EcoPower boiler with > 92% efficiency.
- Full ceramic piston pump.
- Reduced running costs.
- 1450 rpm motor with low noise level.
- Quick Service concept reduces maintenance costs.
- Easy to use control panel... all controls in one place.
- Ergo accessory system for additional user comfort.

| Technical data | Neptune 5-27 | Neptune 5-42 | Neptune 5-49 | Neptune 5-49 X | Neptune 5-5 | Neptune 5-57 X | Neptune 5-57 X |
|--|---------------|---------------|---------------|----------------|---------------|----------------|--------------------|
| PUMP PRESSURE (BAR/MPA) | 110/11 | 170/17 | 180/18 | 180/18 | 200/20 | 200/20 | 200/20 |
| CLEANING IMPACT (KG/FORCE) | 2,7 | 4,2 | 4,9 | 4,9 | 5,7 | 5,7 | 5,7 |
| WATER FLOW QMAX/QIEC (L/H) | 700/630 | 860/800 | 970/900 | 970/900 | 1080/100 | 1080/1000 | 1080/1000 |
| MAX INLET TEMPERATURE (°C) | 40 | 40 | 40 | 40 | 40 | 40 | 40 |
| NUMBER OF PISTONS | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| CERAMIC PISTONS | X | X | X | X | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 80-140 | 80-140 | 80-140 | 80-140 | 80-140 | 80-140 | 80-140 |
| FUEL CONSUMPTION DT 45 °C (KG/H) | 3,1 | 3,9 | 4,3 | 4,3 | 4,8 | 4,8 | 4,8 |
| FUEL TANK (L) | 35 | 35 | 35 | 35 | 35 | 35 | 35 |
| DIMENSIONS LxWxH (MM) | 1190X702X987 | 1190X702X987 | 1190X702X987 | 1190X702X987 | 1190X702X98 | 1190X702X987 | 1190X702X987 |
| WEIGHT (KG) | 175 | 180 | 184 | 189 | 184 | 189 | 189 |
| POWER CONSUMPTION (KW) | 3,3 | 5,6 | 6,9 | 6,9 | 7,9 | 7,9 | 7,9 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/14 | 400/3/50/10 | 400/3/50/12 | 400/3/50/12 | 400/3/50/1 | 400/3/50/13 | 230-400/3/50/24-14 |
| EL. CABLE (M) | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| DETERGENT TANK (L) | A: 15 + B: 10 | A: 15 + B: 10 | A: 15 + B: 10 | A: 15 + B: 10 | A: 15 + B: 10 | A: 15 + B: 10 | A: 15 + B: 10 |
| NOZZLE SIZE | 0450 | 0450 | 0550 | 0550 | 0550 | 0550 | 0550 |

Premium mobile hot water

NEPTUNE 7

The solution for industrial tasks

The tough and robust Neptune 7 series combines low running costs, ease of use, low noise and high cleaning efficiency. The most effective tool for heavy duty, industrial hot water cleaning in any sector.

Product facts

- EcoPower boiler with > 92% efficiency.
- C3 pumps with 4 ceramic pistons.
- Reduced running costs.
- 1450 rpm motor with low noise level.



Technical data

| |
|--|
| PUMP PRESSURE (BAR/MPA) |
| CLEANING IMPACT (KG/FORCE) |
| WATER FLOW QMAX/QIEC (L/H) |
| MAX INLET TEMPERATURE (°C) |
| NUMBER OF PISTONS |
| CERAMIC PISTONS |
| PUMP (RPM) |
| WATER TEMPERATURE (WATER/STEAM) (°C) |
| FUEL CONSUMPTION DT 45 °C (KG/H) |
| FUEL TANK (L) |
| DIMENSIONS LXWXH (MM) |
| WEIGHT (KG) |
| POWER CONSUMPTION (KW) |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) |
| EL CABLE (M) |
| DETERGENT TANK (L) |
| NOZZLE SIZE |

Neptune 7-63

| |
|---------------|
| 175/17,5 |
| 6,3 |
| 1260/1170 |
| 40 |
| 4 |
| X |
| 1450 |
| 100-140 |
| 5,6 |
| 35 |
| 1190X702X987 |
| 217 |
| 8,3 |
| 400/3/50/15 |
| 5 |
| A: 15 + B: 10 |
| 0680 |

Neptune 7-63 X2

| |
|---------------|
| 175/17,5 |
| 6,3 |
| 1260/1170 |
| 40 |
| 4 |
| X |
| 1450 |
| 100-140 |
| 5,6 |
| 35 |
| 1190X702X987 |
| 224 |
| 8,3 |
| 400/3/50/15 |
| 10 |
| A: 15 + B: 10 |
| 0680 |

Premium mobile hot water

NEPTUNE 8



For heavy duty use

The tough and robust Neptune 8 series combines low running costs, ease of use, low noise and high cleaning efficiency. The most effective tool for heavy duty uses requiring high water flow.

Product facts

- EcoPower boiler with > 92% efficiency.
- High water flow pump.
- Reduced running costs.
- 1450 rpm motor with low noise level.
- QuickService concept reduces maintenance costs.
- Easy to use control panel, all controls in one place.
- Ergo accessory system for additional user comfort.
- Use by 1 or 2 people at same time.

Technical data

| |
|--------------------------------------|
| PUMP PRESSURE (BAR/MPA) |
| CLEANING IMPACT (KG/FORCE) |
| WATER FLOW QMAX/QIEC (L/H) |
| MAX INLET TEMPERATURE (°C) |
| NUMBER OF PISTONS |
| CERAMIC PISTONS |
| PUMP (RPM) |
| WATER TEMPERATURE (WATER/STEAM) (°C) |
| FUEL CONSUMPTION DT 45 °C (KG/H) |
| FUEL TANK (L) |

Neptune 8-103

| |
|-----------|
| 180/18 |
| 10,3 |
| 2000/1950 |
| 40 |
| 3 |
| X |
| 1450 |
| 70-140 |
| 9,4 |
| 35 |

Neptune 8-103

| |
|-----------|
| 180/18 |
| 10,3 |
| 2000/1950 |
| 40 |
| 3 |
| X |
| 1450 |
| 70-140 |
| 9,4 |
| 35 |

| | | |
|--|--------------|--------------|
| DIMENSIONS LXWXH (MM) | 1190X702X987 | 1190X702X987 |
| WEIGHT (KG) | 230 | 230 |
| POWER CONSUMPTION (KW) | 12 | 12 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50 | 500/3/50 |
| EL CABLE (M) | 5 | 5 |
| DETERGENT TANK (L) | 15+10 | 15+10 |
| NOZZLE SIZE | 1200 | 1200 |

Medium mobile hot water

NEPTUNE E



Electrical heated hot water unit

The ergonomic and easy to use NEPTuNE design is now adapted to an electrical heated hot water unit. Ideal for use in areas where exhaust gases must be avoided, the Neptune E offers pollution free hot water cleaning.

Product facts

- Pollution free electrical heating.
- 1450 rpm motor with low noise level.
- Quick Service concept reduces maintenance costs.
- Easy to use control panel, all controls in one place.
- Ergo accessory system for additional user comfort.

Technical data

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 150/15 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 750/720 |
| MAX INLET TEMPERATURE (°C) | 70 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| MAX TEMPERATURE (C) | 30-80 |
| DIMENSIONS LXWXH (MM) | 1190X702X987 |
| WEIGHT (KG) | 131 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/27 |
| EL CABLE (M) | 5 |
| NOZZLE SIZE | 0435 |

Neptune e 12

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 150/15 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 750/720 |
| MAX INLET TEMPERATURE (°C) | 70 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| MAX TEMPERATURE (C) | 30-80 |
| DIMENSIONS LXWXH (MM) | 1190X702X987 |
| WEIGHT (KG) | 131 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/27 |
| EL CABLE (M) | 5 |
| NOZZLE SIZE | 0435 |

Neptune e 24

| | |
|--|--------------|
| PUMP PRESSURE (BAR/MPA) | 150/15 |
| CLEANING IMPACT (KG/FORCE) | 3,6 |
| WATER FLOW QMAX/QIEC (L/H) | 750/720 |
| MAX INLET TEMPERATURE (°C) | 70 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| MAX TEMPERATURE (C) | 30-80 |
| DIMENSIONS LXWXH (MM) | 1190X702X987 |
| WEIGHT (KG) | 131 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/42 |
| EL CABLE (M) | 5 |
| NOZZLE SIZE | 0435 |

Stationary cold water

MAXXI 4S



Compact stationary line for everyday cold water cleaning

The new MAXXI 4-73S is ideal for everyday cleaning in agriculture, butchers, bakers, around swimming pools and in garages and car rental companies.

Product facts

- Ceramic pistons for longer working life.
- Simple and easy to use.
- Equipped with hose, lance and spray gun.

| | |
|--|-------------------|
| Technical data | maxi 4-73S |
| PUMP PRESSURE (BAR/MPA) | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 7,3 |
| WATER FLOW QMAX/QIEC (L/H) | 1450/1350 |
| MAX INLET TEMPERATURE (°C) | 60 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 2800 |
| POWER CONSUMPTION (KW) | 9,1 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/15,9 |
| EL CABLE (M) | 5 |
| AUTO STANDBY | X |
| NOZZLE SIZE | 0800 |

Stationary cold water

ALPHA BOOSTER



Compact stationary line for everyday cold water cleaning

The new ALPHA BOOSTER line offers a wide range of models for everyday cleaning in agriculture, butchers, bakers, around swimming pools and in garages and car rental companies. The ALPHA BOOSTER offers powerful cleaning, low sound level and high durability.

Product facts

- Single and three phase versions.
- Quiet, slow running 1450 rpm motors.
- Ceramic pistons for longer working life.
- Simple and easy to use.
- Equipped with hose, lance and spray gun.
- Stainless steel cabinet on ALPHA BOOSTER 5 and ALPHA BOOSTER 8.

| Technical data | alpha Booster 3-26 | alpha Booster 3-41 | alpha Booster 5-27 | alpha Booster 5-49 | alpha Booster 8-103 | alpha Booster 8-103 B |
|--|--------------------|--------------------|--------------------|--------------------|---------------------|-----------------------|
| PUMP PRESSURE (BAR/MPA) | 140/14 | 180/18 | 110/11 | 180/18 | 180/18 | 180/18 |
| CLEANING IMPACT (KG/FORCE) | 2,6 | 4,1 | 2,7 | 4,9 | 10,3 | 10,3 |
| WATER FLOW QMAX/QIEC (L/H) | 600/550 | 825/750 | 700/630 | 970/900 | 2000/1950 | 2000/1950 |
| MAX INLET TEMPERATURE (°C) | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 | 50-60 |
| NUMBER OF PISTONS | 3 | 3 | 3 | 3 | 3 | 3 |
| CERAMIC PISTONS | X | X | X | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 |
| DIMENSIONS LXWXH (MM) | 560X350X370 | 560X350X370 | 643X357X365 | 643X357X365 | 655X425X467 | 655X425X467 |
| WEIGHT (KG) | 39 | 39 | 48 | 48 | 78 | 76 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 230/1/50/15,6 | 400/3/50/9,9 | 230/1/50/15 | 400/3/50/12,5 | 400/3/50/ | 400/3/50/ |
| EL CABLE (M) | 5 | 5 | 5 | 5 | 5 | 5 |

Stationary cold water

UNO BOOSTER



Flexible, reliable and always ready to start

1 pump stationary cold water unit for medium and heavy cleaning applications in agriculture, milking sheds industry, food industry and shipping.

Product facts

- Stainless steel design for added hygiene and protection against corrosion.
- High level of serviceability.
- 70°C inlet water temperature.
- Water break tank.
- Heavy duty C3 pump for long working life.
- PCB for use of factory mounted options on EXTENDED version.

| Technical data | Uno Booster | Uno Booster extended |
|--|---------------|----------------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 5,7 | 5,7 |
| WATER FLOW QMAX/QIEC (L/H) | 1200/1120-540 | 1200/1120-540 |
| MAX INLET TEMPERATURE (°C) | 70 | 70 |
| NUMBER OF PISTONS | 4 | 4 |
| CERAMIC PISTONS | X | X |
| PUMP (RPM) | 1450 | 1450 |
| PUMP | 1 | 1 |
| DIMENSIONS LXWXH (MM) | 370X700X500 | 370X700X500 |
| WEIGHT (KG) | 81 | 81 |
| POWER CONSUMPTION (KW) | 6,7 | 6,7 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/12 | 400/3/50/12 |
| EL CABLE (M) | 4 | 4 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0640 | 0640 |

Stationary cold water

DUO BOOSTER



2-pump stationary cold water unit

2-pump stationary cold water unit for medium and heavy cleaning applications in agriculture, milking sheds industry, food industry and shipping.

Product facts

- 2 pump system for use by 1 or 2 people at same time.
- Stainless steel design for added hygiene and protection against corrosion.
- High level of serviceability.
- 70°C inlet water temperature.
- Water break tank.
- Heavy duty C3 pump for long working life.
- PCB for use of factory mounted options on EXTENDED version.

| Technical data | duo Booster | duo Booster extended |
|--|----------------|----------------------|
| PUMP PRESSURE (BAR/MPA) | 160/16 | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 11,4 | 11,4 |
| WATER FLOW QMAX/QIEC (L/H) | 2400/2240-1120 | 2400/2240-1120 |
| MAX INLET TEMPERATURE (°C) | 70 | 70 |
| NUMBER OF PISTONS | 4 | 4 |
| CERAMIC PISTONS | X | X |
| PUMP (RPM) | 1450 | 1450 |
| NUMBER OF PUMPS | 2 | 2 |
| DIMENSIONS LXWXH (MM) | 370X800X900 | 370X800X900 |
| WEIGHT (KG) | 160 | 160 |
| POWER CONSUMPTION (KW) | 13,5 | 13,5 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/24 | 400/3/50/24 |
| EL CABLE (M) | 4 | 4 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0640 | 0640 |

Stationary cold water

DELTA BOOSTER

The ultimate solution

2 to 6 pump stationary cold water unit for the heaviest cleaning applications in industry, food industry and shipping.

Product facts

- 2 to 6 pumps for up to 6 users at one time.
- Colour coded lances allow mixed use of low, medium and high pressure, detergent application.
- Inlet water of up to 85°C into break tank and 70°C through pumps.
- Stainless steel design with high level of accessibility and serviceability.
- Machine continues to run whilst individual pumps can be removed for service.
- Line pressures from 60 to 200 bar available



| Technical data | Delta Booster 2 Pumps | delta Booster 3 Pumps | delta Booster 4 Pumps | delta Booster 5 Pumps | delta Booster 6 Pumps | delta Booster 3 Pumps | delta Booster 6 Pumps |
|---|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| PUMP PRESSURE (BAR/MPA) 100/10 | 160/16 | 160/16 | 100/10 | 160/16 | 160/16 | | 160/1 |
| CLEANING IMPACT (KG/FORCE) 4,6-13,9 | 5,3-10,6 | 5,3-15,9 | 4,6-27,8 | 5,3-21,3 | | 5,3-26,6 | 5,3-31,8 |
| WATER FLOW QMAX/QIEC (L/H) 1146 | 2080-1040 | 3120-1040 | 4160-1040 | 5200-1040 | 6230-1040 | 3438-1040 | 6876- |
| MAX INLET TEMPERATURE (°C) | 85 | 85 | 85 | 85 | 85 | 85 | 85 |
| NUMBER OF PISTONS | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| CERAMIC PISTONS | X | X | X | X | X | X | X |
| PUMP (RPM) 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 | 1450 |
| NUMBER OF PUMPS | 2 | 3 | 4 | 5 | 6 | 3 | 6 |
| DIMENSIONS LXWXH (MM) 715X790X1800 | 715X790X1800 | 715X790X1800 | 715X790X1800 | 715X790X1800 | 715X790X1800 | 715X790X1800 | 715X790X1800 |
| WEIGHT (KG) 300 | 250 | 300 | 450 | 350 | | 400 | 450 |
| POWER CONSUMPTION (KW) 18,6 40,2 | 13,7 | 20,1 | | 27 | | 33,75 | 40,5 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/23,5 | 400/3/50/35,5 | 400/3/50/47,5 | 400/3/50/58 | 400/3/50/69,5 | 400/3/50/32 | 400/3/50/63,5 |
| AUTO STANDBY X | X | X | X | X | X | X | X |

Stationary hot water

SOLAR BOOSTER DIESEL



Optimal for tough and intense cleaning

Hot water stationary units for tough applications in automotive, industry, shipping and food sectors.

The SOLAR BOOSTER line offers low heating and running costs combined with an easy to use and easy to service design. The onboard PCB permits customizing the machine with factory mounted options.

Product facts

- Expandable control technology with PCB, customization through options.
- Unit diagnosis system.
- Stainless steel design for long life and hygiene.
- Reduced running and service costs.
- Easy to use concept.
- EcoPower boiler with > 92% efficiency.

| Technical data | Solar Booster 5-35 d | Solar Booster 7-51 d | Solar Booster 7-57 d |
|----------------------------|----------------------|----------------------|----------------------|
| PUMP PRESSURE (BAR/MPA) | 125/12,5 | 150/15 | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 3,5 | 5,1 | 5,7 |
| WATER FLOW QMAX/QIEC (L/H) | 835/780 | 1100/1030 | 1200/1110 |

| | | | |
|--|-------------|-------------|---------------|
| MAX INLET TEMPERATURE (°C) | 30 | 30 | 30 |
| NUMBER OF PISTONS | 3 | 4 | 4 |
| CERAMIC PISTONS | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 99 | 99 | 99 |
| FUEL CONSUMPTION DT 45 °C (KG/H) | 3,8 | 4,6 | 4,9 |
| DIMENSIONS LXWXH (MM) | 690X860X950 | | 690X860X950 |
| WEIGHT (KG) | 190 | 215 | 220 |
| POWER CONSUMPTION (KW) | 5,8 | 7,6 | 8,8 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/13 | 400/3/50/13 | 400/3/50/15,5 |
| EL CABLE (M) | 4 | 4 | 4 |
| NOZZLE SIZE | 0530 | 0640 | 0680 |

Stationary hot water

SOLAR BOOSTER ELECTRIC



Optimal for tough and intense cleaning

Hot water stationary units for tough applications in automotive, industry, shipping and food sectors.

The SOLAR BOOSTER line offers low heating and running costs combined with an easy to use and easy to service design. The onboard PCB permits customising the machine with factory mounted options.

Product facts

- Expandable control technology with PCB, customization through options.
- Unit diagnosis system.
- Stainless steel design for long life and hygiene.
- Reduced running and service costs.
- Easy to use concept.
- Electrical heating available from 18 to 60 kW.

| Technical data | Solar Booster 7-37 e | Solar Booster 7-51 e | Solar Booster 7-57 e |
|---|----------------------|----------------------|----------------------|
| PUMP PRESSURE (BAR/MPA) | 125/12,5 | 150/15 | 160/16 |
| CLEANING IMPACT (KG/FORCE) | 3,7 | 5,1 | 5,7 |
| WATER FLOW QMAX/QIEC (L/H) | 875/810 | 1100/103 | 1200/1110 |
| MAX INLET TEMPERATURE (°C) | 85 | 85 | 85 |
| NUMBER OF PISTONS | 4 | 4 | 4 |
| CERAMIC PISTONS | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 |
| WATER TEMPERATURE DELTA T AT FULL FLOW (°C) | 19 | 45 | 14 |
| HEATING CAPACITY (KW) | 18 | 54 | 18 |
| DIMENSIONS LXWXH (MM) | 690X860X950 | 690X860X950 | 690X860X950 |
| WEIGHT (KG) | 175 | 180 | 180 |
| POWER CONSUMPTION (KW) | 5,6 + 18 | 7,7 + 54 | 7,7 + 18 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/9,5+26 | 440/3/60/71 | 400/3/50/13+26 |
| NOZZLE SIZE | 0530 | 0640 | 0680 |

Stationary hot water

SOLAR BOOSTER GAS



Optimal for tough and intense cleaning

Hot water stationary units for tough applications in automotive, industry, shipping and food sectors.

The SOLAR BOOSTER line offers low heating and running costs combined with an easy to use and easy to service design. The onboard PCB permits customizing the machine with factory mounted options.

Product facts

- Expandable control technology with PCB, customization through options.
- Unit diagnosis system.
- Stainless steel design for long life and hygiene.
- Reduced running and service costs.
- Easy to use concept.
- 2 stage economical gas burner.

| Technical data | Solar Booster 5-35 G | Solar Booster 7-57 G | Solar Booster 7-51 GHz |
|---|----------------------|----------------------|------------------------|
| PUMP PRESSURE (BAR/MPA) | 125/12,5 | 160/16 | 150/15 |
| CLEANING IMPACT (KG/FORCE) | 3,5 | 5,7 | 5,1 |
| WATER FLOW QMAX/QIEC (L/H) | 835/780 | 1200/111 | 1100/1030 |
| MAX INLET TEMPERATURE (°C) | 30 | 30 | 85 |
| NUMBER OF PISTONS | 3 | 4 | 4 |
| CERAMIC PISTONS | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 99 | 99 | 85 |
| WATER TEMPERATURE DELTA T AT FULL FLOW (°C) | 88 | 70 | 59 |
| GAS CONSUMPTION (M3/H) | 8,3 | 9,3 | 7,3 |
| DIMENSIONS LXWXH (MM) | 690X860X1250 | 690X860X1250 | 690X860X1250 |
| WEIGHT (KG) | 225 | 235 | 220 |
| POWER CONSUMPTION (KW) | 6,2 | 7,6 | 7,1 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/11 | 400/3/50/16 | 400/3/50/14,5 |
| EL CABLE (M) | 4 | 4 | 4 |
| NOZZLE SIZE | 0530 | | 0680 |
| 064 | | | |

Car Wash Self Service

Stationary hot water

TRUCK BOOSTER



Hot water stationary unit

Hot water stationary unit for permanent placement outside for use in fleet, haulage sectors or in slaughterhouse delivery yards.

Product facts

- Stainless steel robust design against corrosion.
- EcoPower boiler for reduced fuel consumption costs.
- Silent Power, low noise level with 1450 rpm motor pump units.
- Simple control panel with only 4 buttons.
- Ergo 3000 accessories for added user friendliness.
- Internal frost protection down to minus 20°C.

| Technical data | 5-49d | 7-63d |
|--|---------------|---------------|
| PUMP PRESSURE (BAR/MPA) | 180/18 | 175/17,5 |
| CLEANING IMPACT (KG/FORCE) | 4,9 | 6,3 |
| WATER FLOW QMAX/QIEC (L/H) | 970/930 | 1260/1170 |
| MAX INLET TEMPERATURE (°C) | 30 | 30 |
| NUMBER OF PISTONS | 3 | 4 |
| CERAMIC PISTONS | X | X |
| PUMP (RPM) | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 90/140 | 90/140 |
| FUEL TANK (L) | 33 | 33 |
| DIMENSIONS LXWXH (MM) | 1025X715X1670 | 1025X715X1670 |
| WEIGHT (KG) | 275 | 285 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/14 | 400/3/50/16 |
| DETERGENT TANK (L) | 2X25 | 2X25 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0550 | 0680 |

Stationary hot water

AUTO BOOSTER



Hot water self-service unit

Hot water self-service unit for car washing centres, service stations and garages.

Product facts

- Stainless steel robust design against corrosion.
- EcoPower boiler for reduced fuel consumption costs.
- SilentPower. Low noise level with 1450 rpm motor pump units.
- Electrically heated version.
- Up to 5 cleaning programs available.
- Internal frost protection down to minus 20°C.
- Closed circuit frost protection for hose and gun.
- Electronic coiner pre-programmed and with teach mode.
- Spring assisted boom for ease of use.
- Water softener available as option.
- Can be made in oil company colours.
- Compact design with small footprint.

| Technical data | 5-20 diesel heat | 5-20 el. heat |
|--|------------------|---------------|
| PUMP PRESSURE (BAR/MPA) | 100/10 | 100/10 |
| CLEANING IMPACT (KG/FORCE) | 2 | 2 |
| WATER FLOW QMAX/QIEC (L/H) | 500/500 | 500/500 |
| MAX INLET TEMPERATURE (°C) | 30 | 30 |
| NUMBER OF PISTONS | 3 | 3 |
| CERAMIC PISTONS | X | X |
| PUMP (RPM) | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 60 | 60 |
| FUEL CONSUMPTION DT 45 °C (KG/H) | 2, 7 | |
| FUEL TANK (L) | 33 | |
| DIMENSIONS LXWXH (MM) | 1025X715X1670 | 1025X715X1670 |
| WEIGHT (KG) | 285 | 285 |
| POWER CONSUMPTION (KW) | 3 | 3 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50 | 400/3/50 |
| DETERGENT TANK (L) | 3X25 | 3X25 |
| CLEARANCE HEIGHT (M) | 3 | 3 |
| AUTO STANDBY | X | X |
| NOZZLE SIZE | 0370 | 0370 |

Medium mobile hot water

NEPTUNE SB



Self-service version of NEPTUNE 5

The Neptune SB is a self-service version of the award winning Neptune 5, based on the same technology and with coin box for self service use around service stations and garages.

Product facts

- EcoPower boiler with > 92% efficiency.
- Full ceramic piston pump.
- Reduced running costs.
- 1450 rpm motor with low noise level.
- Quick Service concept reduces maintenance costs.
- Easy to use control panel, all controls in one place.
- Ergo accessory system for additional user comfort.

Technical data

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 80/8 |
| CLEANING IMPACT (KG/FORCE) | 2,7 |
| WATER FLOW QMAX/QIEC (L/H) | 860/800 |
| MAX INLET TEMPERATURE (°C) | 40 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 80/- |
| DIMENSIONS LXWXH (MM) | 1190X702X1287 |
| WEIGHT (KG) | 195 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/10 |
| EL CABLE (M) | 5 |
| NOZZLE SIZE | 2508 |

Neptune SB

| | |
|--|---------------|
| PUMP PRESSURE (BAR/MPA) | 80/8 |
| CLEANING IMPACT (KG/FORCE) | 2,7 |
| WATER FLOW QMAX/QIEC (L/H) | 860/800 |
| MAX INLET TEMPERATURE (°C) | 40 |
| NUMBER OF PISTONS | 3 |
| CERAMIC PISTONS | X |
| PUMP (RPM) | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 80/- |
| DIMENSIONS LXWXH (MM) | 1190X702X1287 |
| WEIGHT (KG) | 195 |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | 400/3/50/10 |
| EL CABLE (M) | 5 |
| NOZZLE SIZE | 2508 |

Pressure washers - Petrol driven CONTRACTOR



Heavy duty petrol and diesel driven

The CONTRACTOR line of heavy duty petrol and diesel driven hot water pressure washers are ideal for intense cleaning applications in construction, public or industrial sectors.

Product facts

- Powerful heating system.
- C3 pumps with 4 pistons for heavy duty use.
- Strong and robust steel frame and roll bar for protection.
- Electrical starting system.
- Versions with high flow or high pressure.
- Silent version with sound insulation system.

| Technical data | master Petrol | Silent diesel Water cooled | Standard diesel | heavy duty diesel |
|--|-----------------|-------------------------------|------------------|-------------------|
| PUMP PRESSURE (BAR/MPa) | 220/22 | 200/20 | 180/18 | 210/21 |
| CLEANING IMPACT (KG/FORCE) | 6,1 | 6,9 | 6,2 | 5,6 |
| WATER FLOW QMAX/QIEC (L/H) | 1120/1010 | 1290/1200 | 1230/1140 | 1050/960 |
| MAX INLET TEMPERATURE (°C) | 35 | 35 | 35 | 35 |
| NUMBER OF PISTONS | 4 | 4 | 4 | 4 |
| CERAMIC PISTONS | | X | X | X |
| PUMP (RPM) | 1450 | 1450 | 1450 | 1450 |
| WATER TEMPERATURE (WATER/STEAM) (°C) | 80/150 | 100/150 | 100/150 | 100/150 |
| FUEL CONSUMPTION DT 45 °C (KG/H) | 4,4 | 5,6 | 5,5 | 4,4 |
| FUEL TANK (L) | 20 | 60 | 20 | 20 |
| POWER SOURCE DIESEL | | X | X | X |
| POWER SOURCE PETROL | X | | | |
| DIMENSIONS LXWXH (MM) | 1050X910X860 | 11160X910X1250 | 11160X910X1060 | 11160X910X1060 |
| WEIGHT (KG) | 220 | 510 | 315 | 315 |
| POWER CONSUMPTION (KW) | 9,1KW/13HP | 12,6KW/16,9HP | 12,0KW/16,3HP | 12,0KW/16,3HP |
| VOLTAGE/PHASE/FREQUENCY/CURRENT (V/-/HZ/A) | HONDA GX390 LXE | MITSUBISHI S3L2-61SG | RUGGERINI MD151S | RUGGERINI MD151S |
| SUCTION HEIGHT DRY (M) | 5 | 2 | 5 | 5 |
| NOZZLE SIZE | 0500 | 0640 | 0640 | 0640 |

Brake & part washers

BW 24/35



Mobile brake washers

Mobile brake washer for cleaning of brake and spare parts in garages or workshops.

Product facts

- 24 and 35 litre tank capacity.
- Stainless steel heating tank against corrosion.
- Autonomous cleaning.
- Adjustable cleaning basket.
- Overheating safety valve.

TECHNICAL DATA

| | |
|--|--------------|
| PUMP Pressure (bar/MPa) | 6/0,6 |
| Water Flow QMax/QIEC (l/h) | 90/90 |
| Water temperature (Water/Steam) (°C) | 15-95 |
| Tank Capacity (l) | 24 |
| Hose Length (M) | 2 |
| DIMENSIONS l x W x h (MM) | 445x570x1060 |
| Heating Element (W) | 2000 |
| HEATING Time (MIN) | 35 |
| Wash tray l x W x h (MM) | 550x450x200 |
| Weight (KG) | 40 |
| Voltage/Phase/Frequency/Current (V/-/Hz/a) | 230/1/50/9 |
| Power Consumption (a) | 9,0 |

BW 24

| | |
|--|--------------|
| PUMP Pressure (bar/MPa) | 6/0,6 |
| Water Flow QMax/QIEC (l/h) | 90/90 |
| Water temperature (Water/Steam) (°C) | 15-95 |
| Tank Capacity (l) | 24 |
| Hose Length (M) | 2 |
| DIMENSIONS l x W x h (MM) | 445x570x1060 |
| Heating Element (W) | 2000 |
| HEATING Time (MIN) | 35 |
| Wash tray l x W x h (MM) | 550x450x200 |
| Weight (KG) | 40 |
| Voltage/Phase/Frequency/Current (V/-/Hz/a) | 230/1/50/9 |
| Power Consumption (a) | 9,0 |

BW 35

| | |
|--|--------------|
| PUMP Pressure (bar/MPa) | 6/0,6 |
| Water Flow QMax/QIEC (l/h) | 90/90 |
| Water temperature (Water/Steam) (°C) | 15-95 |
| Tank Capacity (l) | 35 |
| Hose Length (M) | 2 |
| DIMENSIONS l x W x h (MM) | 445x570x1060 |
| Heating Element (W) | 3000 |
| HEATING Time (MIN) | 35 |
| Wash tray l x W x h (MM) | 550x450x200 |
| Weight (KG) | 40 |
| Voltage/Phase/Frequency/Current (V/-/Hz/a) | 230/1/50/13 |
| Power Consumption (a) | 13 |

