

## BHP-series, grip puller sets



- Precise hydraulic control allows fast, efficient and safe pulling
- Grip Puller Sets include:  
700 bar hydraulics: hand pump, hollow cylinder, saddle, hose, gauge and adaptor  
2 and 3-jaw grip pullers

\* **Important:** when using a double crosshead (2 grip arms) or when using puller legs in combination with bearing cup attachments, DO NOT exceed 50% of the rated puller capacity.

Capacity ton (kN)	Grip Puller Set ** including hydraulics Model Nr.	Grip Puller Set *** without hydraulics Model Nr.	Grip Puller Specifications								Set Weight (kg)
			Maximum Spread		Maximum Reach		Jaw Size		Adjusting Screw		
			2-jaws (mm)	3-jaws (mm)	2-jaws (mm)	3-jaws (mm)	Thickness (mm)	Width (mm)	Thread (UN)	Length (mm)	
8 (71)	<b>BHP-152</b>	BHP-1762	249	249	252	252	15	23	3/4"-16	400	22
20 (178)	<b>BHP-251G</b>	BHP-252	400	499	300	300	20	27	1"-8	675	56
30 (267)	<b>BHP-351G</b>	BHP-352	593	800	387	387	24	38	1 1/4"-7	795	91
50 (445)	<b>BHP-551G</b>	BHP-551G	899	1100	700	700	30	39	1 5/8"- 5.5	975	160

\*\* Hydraulic set included. See catalogue page (pdf) for more details.

\*\*\* Mechanical Grip Pullers can be ordered without hydraulic set.