

EP-series, posi lock® mechanical pullers



- Patented 'Safety Cage' guides jaws, holding them securely onto the part
- Safer and faster pulling
- Roll threaded shafts for less effort when applying high torque
- Slim tapered jaws for improved gripping in tight spots
- Available in 2 and 3 jaw design and inside and outside pulling configuration
- More efficient pulling, as one man can do the job where manual pullers often require two operators
- Optional Accessories: Long jaws, ram point sets and lift plates

| Number of Jaws | Maximum Reach (mm) | Spread Range min. - max. (mm) | Capacity ton (kN) | Model Number External Pullers | Model Number Internal Puller | Center Bolt Diameter (mm) | Slide hammer weight (kg) | Weight (kg) |
|----------------|--------------------|-------------------------------|-------------------|-------------------------------|------------------------------|---------------------------|--------------------------|-------------|
| 2 | 101 | 12 - 127 | 2(17) | EP-204 | - | 14 | - | 1,4 |
| 3 | 101 | 12 - 127 | 5 (45) | EP-104 | - | 14 | - | 1,8 |
| 2 | 152 | 12 - 178 | 6 (53) | EP-206 | - | 16 | - | 3,2 |
| 3 | 152 | 12 - 178 | 10 (89) | EP-106 | - | 16 | - | 3,6 |
| 2 | 203 | 19 - 304 | 12 (106) | EP-208 | - | 20 | - | 5,4 |
| 3 | 203 | 19 - 304 | 17 (151) | EP-108 | - | 20 | - | 6,4 |
| 2 | 245 | 25 - 381 | 14 (124) | EP-210 | - | 20 | - | 5,9 |
| 3 | 245 | 25 - 381 | 20 (178) | EP-110 | - | 20 | - | 7,3 |
| 2 | 304 | 63 - 457 | 25 (222) | EP-213 | - | 29 | - | 17,2 |
| 3 | 304 | 63 - 457 | 30 (267) | EP-113 | - | 29 | - | 2,0 |
| 2 | 355 | 76 - 635 | 35 (311) | EP-216 | - | 31 | - | 25,8 |
| 3 | 355 | 76 - 635 | 40 (356) | EP-116 | - | 31 | - | 30,8 |
| 3 * | 218 | 14 - 133 | - | - | EPPMI-6 * | 14,2 | 1,1 | 3,9 |

* EPPMI-6 supplied with 3 standard and 3 long jaws.