

Rotary hammer with SDS-plus

GBH 2-23 RE Professional

The specialist tool for drilling rows of holes

- Robust design, ideal for continuous use
- Hammer mechanism designed for high drilling rate
- Soft grip on main handle and auxiliary handle for a secure hold



- Impact stop for drilling in wood and steel
- Rotating brush plate (for equal power in forward and reverse rotation)
- Overload clutch

Scope of delivery

Part no. 0 611 250 400

- Auxiliary handle (2 602 025 120)
- Depth stop 210 mm (1 613 001 010)
- Carrying case (2 605 438 524)

Voltage, electrical 230 V

Technical data

Rated power input	650 W
Impact energy	0 – 2,5 J
Impact rate at rated speed	0 – 4.400 bpm
Rated speed	0 – 1.000 rpm
Weight without cable	2,3 kg
Tool holder	SDS-plus

Drilling range

Drilling diameter in concrete with hammer drill bits	4 – 23 mm
--	-----------

Optimum range of applications in concrete with hammer drill bits 6 – 12 mm

Max. drilling diameter in masonry with core cutters 68 mm

Max. drilling diameter in steel 13 mm

Max. drilling diameter in wood 30 mm

Functions

- Forward/reverse operation
- Electronic
- Overload clutch