

Rotary hammer with SDS-plus

GBH 4-32 DFR Professional

The fastest multi-hammer in the 4kg class

- Wide range of applications in chiseling and drilling work and when working with a core cutter
- Drills up to 30% faster (25 mm diameter) than other tools in its class
- Low vibration levels of only 10 m/s² for less tiring work due to Bosch Vibration Control



- Extremely robust due to aluminum gear housing
- Extremely fast changing between SDS-plus and keyless chuck for drilling in wood and metal
- Compact design for perfect handling

Scope of delivery

Part no. 0 611 332 100

- Carrying case (2 605 438 651)
- Auxiliary handle (2 602 025 176)
- Depth stop 310 mm (1 613 001 003)
- SDS-plus quick-change chuck (2 608 572 213)

Package (L/W/H) 480 x 360 x 130 mm

Voltage, electrical 230 V

Technical data

Rated power input	900 W
Impact energy	0 – 5 J
Impact rate at rated speed	0 – 3.600 bpm
Rated speed	0 – 800 rpm
Weight without cable	4,7 kg
Tool holder	SDS-plus

Drilling range

Created with

Drilling diameter in concrete with hammer drill bits	6 – 32 mm
Optimum range of applications in concrete with hammer drill bits	14 – 25 mm
Max. drilling diameter in masonry with core cutters	90 mm
Max. drilling diameter in steel	13 mm
Max. drilling diameter in wood	13 mm

Functions

- Forward/reverse operation
- Electronic
- Overload clutch