

Shear

GSC 2.8 Professional

The slim tool with reversible blade

- Slim design with planetary gears
- Reversible blade for particularly high economic efficiency
- Knob grip for comfortable and safe guidance



- Tight curve radius for flexible cuts
- Sliding switch adapted to grip and covered
- Optimum view of cutting line
- Robust design for continuous use
- Powerful 500-watt motor
- Safety switch

Scope of delivery

Part no. 0 601 506 103

- Blade (2 607 010 025)
- Alignment gauge (ET no. 2 607 970 001)
- Allen key KW 5 (ET no. 1 907 950 006)
- Allen key KW 2.5 (ET no. 1 907 950 003)

Package (L/W/H) 330 x 170 x 90 mm

Technical data

Material that can be processed	Steel up to 400 N/mm ² at 2.8 mm
Stroke rate, load	1.500 spm
Stroke rate at no load	2.400 spm
Weight without cable (EPTA standard)	2,7 kg
Length	292 mm
Height	205 mm
Cutting capacity in steel (400 N/mm ²), max.	2,8 mm
Cutting capacity in steel (600 N/mm ²), max.	2,2 mm
Cutting capacity in steel (800 N/mm ²), max.	1,9 mm
Cutting capacity in aluminum (250 N/mm ²), max.	3,5 mm

Electric specifications

Rated power input	500 W
Power output	270 W