

GWS 10-125 Z Professional

- Good handling thanks to slim housing
- Vibration Control auxiliary handle with 40% vibration reduction for low-fatigue working (EN 60745)
- Gear head can be rotated in 90° steps
- Handle can be used on right or left

Part no. 0 601 832 200

- Protective guard (1 605 510 365)
- Backing flange (ET no. 2 605 703 014)
- Locking nut (ET no. 1 603 345 043)
- Two-hole spanner (ET no. 1 607 950 052)
- Vibration Control auxiliary handle (2 602 025 123)

Voltage, electrical 230 V

Technical data

Rated power input	1.000 W
No-load speed	11.000 rpm
Power output	630 W
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight without cable (EPTA standard)	2,0 kg

Functions

- Champion motor
- Anti-rotation protective guard

Noise/vibration information

Show values

Measured values determined according to EN 60745
Total vibration values (vector sum of three directions)

Surface grinding (roughing)

Vibration emission value ah 5,5 m/s²

Uncertainty K 1,5 m/s²

Sanding with sanding sheet

Vibration emission value ah 3,0 m/s²

Uncertainty K 1,5 m/s²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 87 dB(A);
Sound power level 98 dB(A). Uncertainty K= 3 dB.