

GWS 8-115 Professional



- Vibration Control auxiliary handle with 40% vibration reduction for low-fatigue working (EN 60745)
- Direct cooling for high overload capability and long lifetime
- Gear head can be rotated in 90° steps
- Handle can be used on right or left

Technical data

Rated power input	800 W
No-load speed	11.000 rpm
Power output	500 W
Grinding spindle thread	M 14
Disc diameter	115 mm
Rubber sanding plate, diameter	115 mm
Wire cup brush, diameter	70 mm
Length	286 mm
Height	106 mm
Weight without cable (EPTA standard)	1,9 kg

Functions

- Champion motor
- Direct cooling
- Locking system
- Anti-rotation protective guard

Noise/vibration information

Show values

Measured values determined according to EN 60745
Total vibration values (vector sum of three directions)

Surface grinding (roughing)

Vibration emission value ah 5,5 m/s²

Uncertainty K 2,0 m/s²

Sanding with sanding sheet

Vibration emission value ah 3,0 m/s²

Uncertainty K 1,5 m/s²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 91 dB(A); Sound power level 102 dB(A). Uncertainty K= 3 dB.

Part no. 0 601 820 200

- Protective guard (1 605 510 364)
- Vibration Control auxiliary handle (2 602 025 123)
- Backing flange (ET no. 2 605 703 014)
- Locking nut (ET no. 1 603 345 043)
- Two-hole spanner (ET no. 1 607 950 052)

Voltage, electrical 230 V

Package (L/W/H) 360 x 132 x 130 mm