

PR-Series, POW'R RISER Lifting Jack



- 534, 890, 1334 and 1779 kN capacities with pneumatic or electric pumps for the toughest jobs
- 102 mm ground clearance for transport over rail and rough terrain
- Three position handle provides easy tilt back and transport
- Complies with ASME/ANSI B30.1 specifications
- Easy to change external filter minimizes down time
- Rugged, fully enclosed 610 mm wide frame with no exposed fittings or hoses
- SUP-R-STACK™ Extension System allows lifting at all heights without blocking

view *POW'R RISER* video

(or right click here and Save Target As... to download)

Capacity	Stroke	Electric Pump Model Number	Weight	Air Pump	Weight	A	B	C	D	Max. Additional Stack Height Using Opt. Ext. System	Valve Type
kN	mm	115 VAC***	kg		kg	mm	mm	mm	mm	mm	
534	356	PREMB06014L	177	PRAMA06014L	177	610	162	356	102	813*	Manual
	686	PREMB06027L	272	PRAMA06027L	272	940	162	356	102	279	
890	406	PREMB10016L	231	PRAMA10016L	231	660	178	457	102	533**	Manual
	686	PREMB10027L	272	PRAMA10027L	272	940	178	457	102	279	
1334	406	-	-	PRASA10016L	231	660	178	457	102	533**	Pneumatic
	686	-	-	PRASA10027L	272	940	178	457	102	279	
	394	-	-	PRASA15016L	258	660	203	457	127	533**	Manual
	673	-	-	PRASA15027L	321	940	203	457	127	279	
1779	394	PREMB15016L	258	-	-	660	203	457	127	533**	Manual
	673	PREMB15027L	321	-	-	940	203	457	127	279	
1779	394	-	-	PRASA20016L	290	660	241	457	152	533**	Pneumatic
	673	-	-	PRASA20027L	374	940	241	457	152	279	

(PR-Series not available in Canada. Contact Enerpac.)

* Based on one 457 mm and one 279 mm Extension and one 76 mm Spacer.

** Based on one 457 mm Extension and one 76 mm Spacer.

*** For **power source** the following characters should be inserted in the 5th space of the model number.

Ordering Example: Model No. PREMI06014L is a 356 mm stroke, 534 kN model, with a manual valve and a 208-240 VAC, 1-ph electric motor.

- A** Air Pump, 1416 liter/minute, 5,5 bar
- B** 115 VAC, 1ph., 50-60 Hz, 20 A
- E** 208-240 VAC, 1-ph., 50-60 Hz, Euro Plug, 10 A
- I** 208-240 VAC, 1-ph., 50-60 Hz, USA Plug, 10 A
- G** ¹⁾208-240 VAC, 3-ph., 50-60 Hz
- W** ¹⁾380-415 VAC, 3-ph., 50-60 Hz
- J** ¹⁾440-480 VAC, 3-ph., 50-60 Hz
- R** ¹⁾575 VAC, 3-ph., 50-60 Hz

¹⁾Not available for 534 kN capacity