

## CAC, CAPT-series, pivoting t-arms



- Clamping two workpieces with one swing cylinder
- Quick and precise clamp arm positioning
- Two piece design allows for quick and precise positioning of clamp arm
- Allows two parts to be clamped with only one cylinder
- Pivoting of clamp arm in either direction allows for large differences in workpiece height
- CAC-series collar attaches to swing cylinder plunger
- CAPT-series arm attaches to collar and clamps to workpiece
- T-arms are recommended for use on SU, SL, ST and SC-series double-acting swing cylinders

Clamp Arm Length	Clamping Force	For Swing Cylinder	Pivoting T-arms Model Number	
Lmax	Ft	Series: SU, SL, ST, SC	Collar	T-Arm
(mm)	(kN)			
	max. - min.			
152	2 x 2,8	52	<a href="#">CAC-52</a>	<a href="#">CAPT-52</a>
203	2 x 4,5	92	<a href="#">CAC-92</a>	<a href="#">CAPT-92</a>
203	2 x 5,8	122	<a href="#">CAC-122</a>	<a href="#">CAPT-122</a>
203	2 x 9,3	202	<a href="#">CAC-202</a>	<a href="#">CAPT-202</a>
228	2 x 16,9	352	<a href="#">CAC-352</a>	<a href="#">CAPT-352</a>