

## Thin Cut-Offs for Angle Grinders - Thin Cut-Off Wheels Type 27 - Cut-Off Wheel Test Pak -Type 27

PFERD Grinding & Cut-off Wheels offer world-leading performance. For free-hand, portable, chop and stationary saws.

PFERD thin wheels cut faster than conventional wheels, leaving a cleaner cut, with minimal burr. Thin cut-off wheels are ideally suited for thin gauge sheet stock, thin walled tubing and small diameter cross sections. Material should always be cut at a right angle to the work piece. Larger work pieces require thicker PFERD cut-off wheels for improved lateral stability.

PFERD manufactures a wide selection of high performance depressed center (type 27) thin cut-off wheels to suit all needs from low purchase price to highest level of performance attainable. Usage Tip:

- .040 thickness recommended for sheet stock and tube 19 gauge and higher
- .045 thickness recommended for 14-18 gauge material
- For larger cross sections, please use 3/32 and larger cut-off wheels for performance and safety.

Not sure which performance level is right for your application? Pick up a test pak and put them to the test on your grinder!



EDP	Diameter	Thickness (Inches)	Arbor Hole	Shape/Form	Grit	Max. RPM	Contents	
69760	4-1/2	.045	7/8	Depressed Center (Type 27)	46	13,300	63162, 63167, 63172	<a href="#">Request Info</a>
69761	5	.045	7/8	Depressed Center (Type 27)	46	12,200	63163, 63168, 63173	<a href="#">Request Info</a>
69762	6	.045	7/8	Depressed Center (Type 27)	46	10,200	63164, 63169, 63174	<a href="#">Request Info</a>